



Empowering you to work smarter

NRDD Recovery Unit



MASTER SERIES

Light • Fast • Compact



DC Motor

- Light
- More efficient

Large Backlit Display

- Easy to read large LCD display
- Backlit display for clarity

Twin Cylinder with 2-Row Oversized Condenser

- Fast recovery

Oil-free Compressor

- Suitable for all commonly used refrigerants

Self-purge Function

- Prevent mixing of various refrigerants

Model		NRDD			
Refrigerant Type		Category III: R-12, R-134a, R-401C, R-500 Category IV: R-22, R-401A, R-401B, R-402B, R-407C, R-407D, R-408A, R-409A, R-411A, R-411B, R-412A, R-502, R-509 Category V: R-402A, R-404A, R-407A, R-407B, R-410A, R-507			
Power Supply	V / Hz	115V/60Hz			
Motor	HP	1			
Max Current Draw	A	10			
Compressor		Oil-less, Air-cooled, Piston style			
Automatic Safety Shut-Off		558 psi / 38.5 bar			
Recovery Rate	lbs / min		R-22	R-134a	R-410a
		High Temp Vapor			
		Direct Vapor	0.73	0.64	0.70
		Direct Liquid	6.94	6.28	9.26
		Push/pull Liquid			
Dimension	in	14.6" × 9.9" × 11.7"			
Weight	lbs	25.4			