

Sharp/NEC Projected Capacitive Touch screen Displays

About the Infrared Solution

Sharp/NEC's line of projected capacitive (PCAP) touch displays are engineered to create maximum visual impact and interactive capabilities through seamless simplicity. The display with integrated touch will ship as a complete solution directly to the end user. PCAP technology allows for ultra-fast response times, 40-point of simultaneous touch, and full HID compliance for plug and play connectivity.



Multi-Touch Screen

True multi-touch support with up to forty simultaneous touch points for all major operating systems



Superior Design

Zero bezel flat front, anti-glare touch screen, excellent optical performance



18/7 Runtime

Around the clock functionality



HID Compliant

Maximum compatibility with numerous operating systems, plug-and-play



Ultra-Fast

Response time allows for split second reactions between touch point and screen. Rapid and smooth touch response



Thermoplastic Seal

Eliminates any gap between bezel and glass, providing a no harborage seal



Easy to Clean

Water and dust resistant



Tempered Glass

In the event of a glass failure, tempered glass breaks down into pebbles rather than shards, leaving a minimal safety hazard.

43"



50"



55"




65"



Part Number		ME431-PT	ME501-PT	ME551-PT	ME651-PT
Glass	SIZE	43"	50"	55"	65"
	Thickness	4mm			
	Type	Tempered			
	Light transmission	TPLuminousness is 83%			
Touch	Touch Tecnology	Projected Capacitive			
	Number of Touches	40-Point (limitations with MacOS, Linux, and Android)			
	Response Time	8 ms			
	Touch Method	Finger or gloved hand			
	Data Interface	HID via USB 2.0			
	Accuracy	0.1% of sensor diagonal			
Power Supply Mode		Single USB connection (5v, 1A)			
Runtime		18/7			
Aspect Ratio		16:9			
Orientation		Portrait / Landscape			
Width/Height/Depth Including Monitor		39.17 x 23.3 x 3.36 in. / 994.85 x 595.49 x 85.34 mm	46.04 x 27.17 x 2.88 in. / 1169.55 x 690.05 x 73.10 mm	50.33 x 29.52 x 3.02 in. / 1,278.45 x 749.90 x 76.80 mm	60.07 x 35.47 x 4.035 in. / 1 525.95 x 900.85 x 102.50 mm
Total Net Weight		57.1 lbs. / 25.9 kg.	75.5 lbs. / 34.32 kg.	81.4 lbs. / 37 kg.	125 lbs. / 56.7 kg.
CONNECTIVITY	Input Terminals	Digital	HDMI 2.0 x2, DP 1.2 x1		
		Analog	N/A		
		Audio	N/A		
		External Control	LAN (100Mbit), 3.5mm Mini Jack IR Remote, RS-232C		
	Output Terminals	Data	USB 2.0 (5V/2A, Media Player)		
		Digital	N/A		
		Analog	N/A		
		Audio	3.5mm Mini Jack		
External Control	N/A				
Supported Operating Systems		Windows 10, 8, 7, Ubuntu 12.04, Linux, Android, Chrome OS, Mac OS X Yosemite (single touch support or multi-touch support through TUIO bridge)			
Ships With		3m Power cord, 2.0m HDMI cable, Wireless remote control, Batteries, Setup Guide			
Other Accessories		SDM-VICW-IS PC Option Card, SDM-VI3W-IS (49"+ Only), SDM-VISW-IS (49"+ Only), SDM-12GSDI Option Card, SDM-HDBT Option Card, Raspberry Pi Compute Module 4 with optional NEC Interface Board (MPi4E), Human Sensor (KT-RC3)			

Solution Sizes Available



Dimensions shown in mm
Projected Capacitive Touch Screen Overlay Patent Pending

All other brand or product names are trademarks or registered trademarks of their respective holders. Product specifications subject to change.

©2022 Sharp NEC Display Solutions of America, Inc. | All rights reserved.

Rev. 09.06.2022