

NH5S Charging Hose Set w/o Ball Valve



NH5R NH5B NH5Y NH5L Individual Charging Hose w/o Ball Valve



NH5SC Charging Hose Set with Ball Valve



NH5CR NH5CB NH5CY Individual Charging Hose with Ball Valve



1/4" Color Hoses, 5 Ft Long

Main Features for All Models


- Suitable for R-410A, R-134a, R-22 and other refrigerants
- 1/4" SAE fittings with 45° bend on one end
- Leak-proof eight-sided crimp
- 800 psi working pressure, 4000 psi burst pressure
- Universal, replaceable gasket
- Adjustable depressor

Ball Valve Models

- Ball valve for reduced refrigerant loss
- Metal valve handle

NH5L

- Reverse threaded for A2L



The valve core depressor can be adjusted up or down to optimize its access to valve core. Use a valve core depressor adjuster to turn the depressor. To lower, turn clockwise; to raise, turn counterclockwise.



Model	NH5S	NH5R	NH5B	NH5Y	NH5L	NH5SC	NH5CR	NH5CB	NH5CY	
Color	Red, Yellow, Blue	Red	Blue	Yellow	Orange	Red, Yellow, Blue	Red	Blue	Yellow	
Quantity	pc 3	1	1	1	1	3	1	1	1	
Ball Valve	Without ball valve					With ball valve				
Pressure Scale	psi				0-800 psi					
Length	ft				5					
Connector	in				1/4" - 1/4"					

1-YEAR WARRANTY