

Primary Device Attributes

| Feature | LinkRunner G2 | LinkRunner AT 2000 | LinkRunner AT 1000 |
|--|---------------|--------------------|--------------------|
| Android™-based ¹ Smart Tester | ● | ✘ | ✘ |
| Android-based App Support via NETSCOUT® App Store | ● | ✘ | ✘ |
| On-board Chrome web browser | ● | ✘ | ✘ |
| On-board Adobe .pdf reader | ● | ✘ | ✘ |
| Speaker, mic, camera, flashlight, accelerometer, compass, gyro | ● | ✘ | ✘ |
| USB | ● | ✘ | ✘ |
| Micro USB | ● | ✘ | ✘ |
| Micro SD | ● | ✘ | ✘ |
| Large color display | ● | ✘ | ✘ |
| Touch Screen | ● | ✘ | ✘ |
| Extensible Platform | ● | ✘ | ✘ |
| Wi-Fi Capable | ● | ✘ | ✘ |
| Bluetooth/BLE Capable | ● | ✘ | ✘ |
| 10/100/1000BASE-T Copper | ● | ● | ● |
| 100/1000BASE-X Fiber | ● | ● | ✘ |
| Line rate packet reflector 1000BASE-T | ● | ● | ✘ |
| IPv6 support | ● | ● | ✘ |

● = Included ✘ = Not Included

Power

| Feature | LinkRunner G2 | LinkRunner AT 2000 | LinkRunner AT 1000 |
|----------------------------------|---------------|--------------------|--------------------|
| Charge off PoE | ● | ✘ | ✘ |
| Lithium ION rechargeable battery | ● | ● | Option |
| AA battery pack | ✘ | Option | ● |

Standard Test

| Feature | LinkRunner G2 | LinkRunner AT 2000 | LinkRunner AT 1000 |
|---|---------------|--------------------|--------------------|
| Negotiate PoE voltage (802.3at) | • | • | • |
| Negotiate PoE voltage (uPoe, 802.3bt) | • | x | x |
| TruePower™ PoE load (25.5W) | • | • | x |
| TruePower™ PoE load up to 802.3bt (71W) | • | x | x |
| DHCP offer/response | • | • | • |
| DHCP Option 43, 60, 150 | • | x | x |
| 1000BASE-T downshift warning | • | x | x |
| IP Address assignment | • | • | • |
| Proxy Configuration | • | • | • |
| Nearest switch (CDP/LLDP) | • | • | • |
| DNS server response support (2) | • | • | • |
| DNS server response support (4) | • | x | x |
| Gateway Router | • | • | • |
| VLAN Traffic Distribution | • | x | x |
| Public facing IP address | • | x | x |
| Ping or TCP Port Open Reachability | • | • | • |
| Continuous Ping | • | • | • |

Cable Test

| Feature | LinkRunner G2 | LinkRunner AT 2000 | LinkRunner AT 1000 |
|--|---------------|--------------------|--------------------|
| Distance to fault | • | • | • |
| Flash switch port | • | • | • |
| Integrated patch cable test | • | • | • |
| WireView support | • | • | • |
| Toning (analog and IntelliTone™ 200 Probe ²) | • | • | • |

Configurable

| Feature | LinkRunner G2 | LinkRunner AT 2000 | LinkRunner AT 1000 |
|--------------------------------------|---------------|--------------------|--------------------|
| Proxy | • | • | • |
| DHCP or Static IP Support | • | • | • |
| Configurable PoE, Link, MAC and VLAN | • | • | • |
| Configurable 802.1X security | • | • | • |

Reports

| Feature | LinkRunner G2 | LinkRunner AT 2000 | LinkRunner AT 1000 |
|------------------------------------|---------------|--------------------|--------------------|
| Results saved locally on tester | Unlimited | 50 | 10 |
| LinkRunner™ AT Manager PC software | x | • | • |
| Link-Live Cloud Reporting | • | • | • |

¹ Android is a trademark of Google Inc.

² IntelliTone is a registered trademark of Fluke Corporation.

© 2018 NETSCOUT SYSTEMS, INC. All rights reserved. NETSCOUT, the NETSCOUT logo, Guardians of the Connected World, Adaptive Service Intelligence, Arbor Networks, the Arbor Networks logo, ATLAS, InfiniStream, InfiniStreamNG, nGenius, and nGeniusONE are registered trademarks or trademarks of NETSCOUT SYSTEMS, INC., and/or its subsidiaries and/or affiliates in the USA and/or other countries. Third-party trademarks mentioned are the property of their respective owners.