

newline TANGO




Connect
with USB



Plug & Play
Design



1080p
Camera



120°
Field of View



Integrated
Microphone



Digital Noise
Reduction

PLUG, PLAY, **CONNECT** WITH STYLE

Newline Tango brings you simple video connectivity with any device, including your Newline display. Be UC-ready in a flash by adding the 1080p HD camera to any Newline display. Newline Tango works with any video software including Zoom, Meet, Teams, Webex, and more. With an integrated microphone, digital noise reduction, and a wide-angle field of view, be seen and heard from anywhere in the room. Whether you're connecting to your remote students in your classroom or hosting virtual meetings with your team, Newline Tango is here to boost your videoconferencing with style.

TANGO

Model	
TANGO-CAM	
Camera	
Sensor	1/2.7", CMOS, total pixel : 2 Mega
Scanning Mode	Progressive
Lens Mount	M12
Lense	focus: f=3.1mm, FOV: 119°
Minimal Illumination	0.5 Lux @ (F1.8, AGC ON)
Shutter	1/30s ~ 1/10000s
Digital Noise Reduction	2D, 3D digital noise reduction
Backlight Compensation	Yes
Microphone	
Pickup Range	11.8 ft
Direction	Omni-directional
Noise Cancellation	Yes
Automatic Gain Control	Yes
USB Specification	
Compatible Operating System	Windows® 7 (1080P and under only), Windows 8.1, Windows 10 or higher; macOS™ 10.10 or higher; Google™ Chromebook™ Version 29.0.1547.70 or higher; Linux (UVC supported)
Hardware Requirements	2.4 GHz Intel® Core 2 Duo processor or higher; 2 GB RAM or more; USB 2.0 port (USB 3.0 required for 4K)
Color System/Compression	H.264 / MJPEG / YUY2
Video Format	1080p@30fps/25fps, 720p@30fps/25fps, 960x540p@30fps/25fps, 640x360p@30fps/25fps
USB Video Communicaiton Protocol	UVC v1.0
General Specification	
Input Voltage	5V (USB Power)
Power Consumption	< 1.4W
Dimensions	7.6 x 1.8 x 5.3 in
Net Weight	0.47 lbs
Operating Temperature	14°F ~ 104°F
Storage Temperature	-40°F ~ 140°F
Mounting Options	Panel, desktop or tri-pod