

# SELF POWERED SPEAKER/AMPLIFIER

3 Source, 5", Integratable

ARCHITECTS AND ENGINEERS  
SPECIFICATIONS / TECHNICAL DATA

## GENERAL SPECIFICATIONS



MODEL NUMBER: AMP-HD2SIC5	
<b>ELECTRICAL AMPLIFIER:</b>	
Input voltage, nominal	(25 watts) 15 volts DC
Input current, operating (15VDC)	1.45 amperes peak
Input volt-amperes, peak (15VDC)	22 volt-amperes
Input voltage, maximum	16.5 volts, DC
<b>Frequency Response,</b>	
EQ set to flat	20Hz to 20 kHz
Bass	±10dB@50Hz
Treble	±10dB@10kHz
THD + Noise	<1% at 13.5 watts, "A" weighted
S/N	>82 dB
Max Power Output (28V in)	40 watts
DC Power, Standby	1.4 watts
AC Power, Sleep Mode	1.4 watts
<b>DC Power,</b>	
Short Circuit protected	Yes
Over current protected	Yes
Over voltage protected	Yes
Over temperature protected	Yes
Minimum Load Impedance	4.0 Ω (Two 8 Ω Speakers in parallel)
Minimum Input impedance, Priority in	10,000 Ω
Minimum Input impedance, RJ45 in	150,000 Ω
Minimum Input impedance, mini-jack	37,000 Ω
Min. Input Impedance, Mini-Jack:	2300 Ω
Woofer Size:	5.25 Inches
Weight of Amplifier/Speaker:	2.55 Lbs.
Height of Amplifier/Speaker:	4 Inches
Backcan:	UL Listed Enclosure (Available)
Tile Bridge:	UL Listed Support Truss (Available)
Warranty:	1 Year

\*\*Mechanical "UL Rating" is dependent upon use of the Backcan and Tile Bridge.

Note: Maximum power requires the replacement of the 15 Volt supply with a 22 Volt supply and Energy Star and UL approvals no longer apply.



**OWI Incorporated**

17141 Kingsview Avenue, Carson, CA 90746 USA

Tel: 310.515.1900

Toll Free: 800.638.1694

Fax: 310.515.1606

Web: [www.owi-inc.com](http://www.owi-inc.com)

E-mail: [info@owi-inc.com](mailto:info@owi-inc.com)

