

P5278P
P6278P
P8378P

PATIO BLASTERS P-SERIES SPEAKERS

SURFACE MOUNT, INDOOR / OUTDOOR SPEAKERS
70 V OR 8 Ω AND UP TO 80 W POWER



P5278P

5", 2-Way, Ported
70 V and 8 Ω
40 W Max Power
2.5, 5, 10, 20 W Taps

P6278P

6.5", 2-Way, Ported
70 V and 8 Ω
45 W Max. Power
3.5, 7.5, 15, 30 W Taps

P8378P

8", 3-Way, Ported
70 /100 V and 8 Ω
80 W Max. Power
5, 10, 20, 40 W Taps

- Outdoor / Indoor Speaker
- Weatherized Aluminum Grill and Bracket
- "U" Mount Bracket Included
- Ceiling and Wall Mount Possibilities
- Black and White Colors Available



OWI[®]
OWI Incorporated
Established 1976

PATIO BLASTERS P-SERIES SPEAKERS

SURFACE MOUNT, INDOOR / OUTDOOR SPEAKERS
70 V OR 8 Ω AND UP TO 80 W POWER



P5278P - 5", 2-WAY, PORTED P6278P - 6.5", 2-WAY, PORTED P8278P - 8", 3-WAY, PORTED

OWI P-Series speakers are suitable for all indoor or outdoor applications where a selection of loudspeaker size is desired. Perfect for restaurants, patios, hotels, parking lots and retail centers.

GENERAL SPECIFICATIONS

MODEL NUMBER:	P5278P	P6278P	P8378P
Description:	5", 2-Way, Ported	6.5", 2-Way, Ported	8", 3-Way, Ported
Outdoor (Covered):	Yes	Yes	Yes
Impedance:	70 V and 8 Ω	70 V and 8 Ω	70/100 V and 8 Ω
Sensitivity (1W/1M):	87 dB + 3 dB	86 dB + 3 dB	89 dB + 3 dB
Max Power:	40 Watts	45 Watts	80 Watts
Nominal Power:	2.5, 5, 10, 20 Watts	3.5, 7.5, 15, 30 Watts	5, 10, 20, 40 Watts
Frequency Response:	75 Hz – 20 kHz	65 Hz – 20 kHz	50 Hz – 20 kHz
Crossover:	4 kHz	3.5 kHz	4 kHz
Dispersion:	120°	92°	85°
High Frequency Driver:	3/4", Dome	2", Dome	25 mm Silk
Low Frequency Driver:	5", Polypropylene/Rubber	6 1/2", Polypropylene/Rubber	8", Polypropylene/Rubber
Woofer Size:	5"	6 1/2"	8"
Woofer Material:	Polypropylene/Rubber	Polypropylene/Rubber	Polypropylene/Rubber
Tweeter(s)	1 Each	1 Each	2 Each
Tweeter Size:	3/4"	2"	2" and 25 mm
Tweeter Material:	Poly Carbonate	PEI	Titanium and Silk
Speaker Wire Connection:	Spring Clips	5-Way Binding Post	5-Way Binding Post
Grill Material:	Aluminum	Aluminum	Aluminum
Enclosure:	Plastic	Plastic	Plastic
Dimensions: (LxWxH/Inches)	7 1/4" x 7 1/8" x 9 3/4"	9 1/2" x 8 1/2" x 1 1 1/4"	12 1/8" x 10 1/2" x 1 4 1/8"
Weight (Pounds):	5.25 Lbs.	9.3 Lbs.	17.2 Lbs.
Color(s):	Black, White	Black, White	Black, White
Paintable:	Yes	Yes	Yes

RECOMMENDED OWI AMPLIFIERS



AMP1SGB



CRS201



Digital Mini Amplifiers
AMPMA40X
AMPMA70V40

OPTIONAL ACCESSORIES

IN-GROUND STAINLESS STEEL STAKE (36")
SS-36

70 VOLT ATTENUATOR

OWI1070M: Mono Attenuator, 70 V, 10 W

OWI2570SW: Stereo Attenuator, 70 V, 25 W



For Additional Information
Go to owi-inc.com/sidemenu/p-series-speakers
or scan code at right
on your smart phone

