WaveTester / WaveSource 850/1300 Test Kit

SKU: KIT-WT-WSMDxx (see connector options below)

Overview

Many fiber optic network bids and Requests For Quote (RFQ) are citing cabling standards to specify the set of guidelines (such as fiber length) that the network installer must follow during the network installation. Adherence to such standards is meant to ensure the quality of the installation and guarantee that the network will perform as it was designed.

The process of testing a network installation to ensure its adherence to specified standards is called certification, and often requires hard-copy documentation as proof of adherence to standards.

The *WaveTester / WaveSource 850/1300 Test Kit* contains the tools necessary for certifying fiber optic links against a myriad of popular cabling standards in multimode networks.

The *WaveTester optical power meter* is multimode and singlemode ready, and can store reference values for all wavelengths used for optical loss measurements. Up to 200 fiber runs may be stored, and downloaded via a PC serial port for report generation using our OWL Reporter software.

The *WaveSource 850/1300* is a multimode light source. Its dual wavelength outputs (850 nm & 1300 nm) are temperature-stabilized for accurate measurements. Two connector options are available (STorSC).



Features

Certification of multimode fiber links at 850 nm and 1300 nm

Auto-test functions store references and data points automatically

Data storage for up to 200 data points

USB interface for continuous data logging, report printing, or data downloading

Multimode Fiber Certification Test Kit

OWL Reporter software for printing formatted fiber certification reports

Measurement modes include absolute (for optical power) or relative (for optical loss)

Selectively view, delete or resample data points

Supported Cabling Standards:

EIA/TIA 568-B ISO/IEC 11801 10-Gigabit Ethernet

1000Base-SX 1000Base-LX 100Base-FX

10Base-FB 10Base-FL FDDI

ATM-155 ATM-622 Fibre Channel

Token Ring

Additional Power Meter Calibrated Wavelengths:


1310nm 1550nm



N.I.S.T. Traceable

Product manuals come in PDF format on CD. Adobe Acrobat Reader $^{\rm IM}$ is required to view these documents.

Patch cables are available for an additional charge. Contact OWL for more information.



Power Meter: WaveTester

Light Source: WaveSource 850/1300

Accessories: OWL Reporter software (on CD)

Product manuals (on CD)

Download cable 9-volt batteries NIST certificate Carrying case

Protective rubber boots

Lanyards



O. W. L. MANUFACTURER OF QUALITY OPTICAL FIBER TEST EQUIPMENT



WaveTester / WaveSource 850/1300 Test Kit

SKU: KIT-WT-WSMDxx (see connector options below)

Specifications

wave lester Optical Power Meter	
Detector Type	InGaAs

NIST Traceable 850 nm, 1300nm, 1310 nm Wavelengths 1550nm

 Measurement Range
 +5 to -60 dBm

 Accuracy
 ±0.15 dB

 Resolution
 0.01 dB

Connector Type 2.5mm Universal

Data Storage Points up to 200

Download Data Points OWL Reporter Software

Power Units Displayed dBm, dB, µW

Battery Life 250 hrs. (9v alkaline)

Backlight Yes
NIST Traceable Yes
Auto-shutdown Yes

Operating Temperature -10 to 55 C Storage Temperature -30 to 70 C

 Width
 2.75"

 Height
 4.94"

 Depth
 1.28"

 Weight
 154g

Conforms to the Harmonized European Standards EN 61326-1 and EN 61010-1.

WaveSource 850/1300 Multimode Light Source Launch Method LED Connector ST or SC Center Wavelength (850 nm) 850 +30/-10 nm 1300 ±50 nm Center Wavelength (1300 nm) Spectral Width (FWHM; 850 nm) 50 nm Spectral Width (FWHM; 1300 nm) 180 nm **Output Power** -20.0 dBm **Initial Accuracy** 0.1 dB Fiber Type multimode **Battery Capacity Display** Yes **Operating Temperature** -20 to +70° C **Storage Temperature** -40 to +85° C 2.75" Width Height 4.94" 1.28" Depth Weight 154q

Conforms to the Harmonized European Standards EN 61326-1 and EN 61010-1.

