

# 4K Wireless Display & Presentation System

## QuickCast Pro-4K



### Easily broadcast 4K sources wirelessly



Easily share content from HDMI sources wirelessly via the Optoma Quickcast Pro. Simply connect the QuickCast Pro receiver to an HDMI input and plug the HDMI transmitter into the source and begin wirelessly transmitting office documents, presentations, videos and digital content with the click of a button.

The HDMI transmitter features an integrated battery with up to 6 hours of battery life for crystal clear digital video and presentations without being tethered to a power adapter. Operating on 802.11ac MIMO technology on a 5 GHz frequency ensures maximum connection stability with minimal interference signal interference up to 30-feet away.

### SUPPORTED DEVICES

<b>PC</b>	Windows 7, 8, 8.1 & 10
<b>Mac</b>	Mac OS X 10.11.x or higher
<b>iOS</b>	iOS 11.x or higher (iPhone, iPad and iPad Pro)
<b>Android</b>	Android 6.x or higher (smartphones and tablets)
<b>Devices</b>	UHD Blu-ray, Blu-ray players, FireTV, AppleTV, Roku, Chromecast and other HDMI devices (streaming sticks require male-to-male HDMI coupler).
<b>Protected Content Support</b>	Netflix, Hulu, Vudu, HBO Go, Amazon Prime Video and other protected digital content

### TECHNICAL SPECIFICATIONS

<b>Native Resolution</b>	4K UHD (3840 x 2160)
<b>Maximum Resolution</b>	4K UHD (3840 x 2160)
<b>Wireless Display Features</b>	Screen mirroring, side-by-side, Samsung Dex
<b>EDID</b>	Auto EDID
<b>Audio</b>	2-channel PCM (stereo)
<b>Video Encoder &amp; Decoder</b>	H.264
<b>Latency</b>	250ms
<b>Operating Room Temperature</b>	41-104°F (5-40°C), 85% max humidity
<b>Power Supply</b>	AC input 100-240V, 50-60Hz, auto-switching

### HDMI TRANSMITTER SPECIFICATIONS

<b>Connectivity</b>	HDMI 1.4 (HDCP 1.4)
<b>Wireless Display Technology</b>	802.11ac MIMO (5 GHz)
<b>Power Source</b>	USB-C (5V, 2-amps) Internal battery
<b>Power Consumption</b>	550mA
<b>Battery Life</b>	6 hours
<b>Battery Charge Time</b>	4 hours
<b>Battery Capacity</b>	3500mAh

### HDMI RECEIVER SPECIFICATIONS

<b>Connectivity</b>	HDMI 2.0 (HDCP 2.2)
<b>Wireless Display Technology</b>	802.11ac MIMO (5 GHz)
<b>Power Source</b>	DC power adapter (5V, 2-amps)
<b>Power Consumption</b>	750mA
<b>Receiving Distance</b>	30ft (10M)

### PHYSICAL SPECIFICATIONS

<b>Weight</b>	HDMI receiver: 2.2 oz. HDMI transmitter: 4.3 oz.
<b>Dimensions (W x H x D)</b>	HDMI receiver: 2.8" x 0.9" x 6.7" HDMI transmitter: 2.8" x 1.2" x 6.7"



\*Optional cradle accessory available

### AVAILABLE BUNDLES & SKUS

QuickCast Pro 4K	SKU	HDMI Receiver	HDMI Transmitter
<b>HDMI Starter Kit</b>	QCP-SK-4K-HDMI	✓	✓
<b>HDMI Receiver</b>	QCP-4K-HDMIRX	✓	
<b>HDMI Transmitter</b>	QCP-4K-HDMITX		✓

#### Warranty

1-year limited warranty

#### What's in the Box

Varies by bundle or SKU.

#### Part Numbers and UPC

HDMI Starter Kit (QCP-SK-4K-HDMI): UPC: 796435 09 156 3

#### Replacement Receiver/Transmitter and Accessories

HDMI Receiver (QCP-4K-HDMIRX): UPC: 796435 09 153 8

HDMI Transmitter (QCP-4K-HDMITX): UPC: 796435 09 150 7

Cradle accessory (QCP-CRADLE): UPC: 796435 09 158 3

Optoma.com



Copyright © 2019 Optoma Technology, Inc. All specifications subject to change at any time.  
\*Optional cradle accessory sold separately. 12112019