

ZU1700

High brightness professional WUXGA laser projector



- **17,000 lumen WUXGA DLP laser projector**
- **Optional lenses allowing for installation flexibility**
- **Ultimate reliability with built in redundancy mode**
- **Pure engine video processing and color matching**

The ZU1700 offers enhanced features such as DuraCore Laser technology. As part of the DuraCore laser line up, it combines longer-lifetime light source and an independent IP rated dust certification for ultimate peace of mind.

Delivering an astonishing 30,000 hours, this projector achieves superior color rendition producing visually striking lifelike images with exceptional detail.

Designed for even the most complex professional installations, the ZU1700 offers a selection of interchangeable lens options for ultimate flexibility.

Designed for high end installations with a multitude of connectivity options and failsafe redundancy mode.

Specifications

The following specifications are preliminary and subject to change without notice

Display/image

| | |
|---------------------------|-------------------|
| Display technology | DLP |
| Resolution | WUXGA (1920x1200) |
| Brightness | 17,000 lumens |
| ANSI brightness | 14,500 lumens |
| Contrast ratio | 2,000,000:1 |
| Native aspect ratio | 16:10 |
| Aspect ratio - compatible | 16:9, 16:10 |
| Screen size | Dependent on lens |

Lamp info

| | |
|-------------------|----------------|
| Light source type | DuraCore Laser |
| LASER life | 30,000 hours |

Optical

| | |
|---------------------|-------------------|
| Throw ratio | Dependent on lens |
| Projection distance | Dependent on lens |

Connectivity

| | |
|-------------|--|
| Connections | Inputs 1 x RS232, 1 x 3D sync, 1 x Wired remote, 1 x HDBaseT, 1 x DisplayPort, 2 x HDMI, 1 x VGA, 1 x DVI-D, 1 x 3G-SDI Outputs 1 x RS232, 1 x 3D sync, 1 x Wired remote, 1 x HDMI, 1 x 3G-SDI Control 1 x RJ45, 1 x USB-A service, 1 x 12V trigger |
|-------------|--|

General

| | |
|-------------------------|----------------------|
| 3D | Full 3D |
| IP rating | IP5X |
| OSD / display languages | 2 languages: English |
| 24/7 operation | Yes |
| 360° operation | Yes |
| Remote control | Backlit ProAV remote |

Networking

| | |
|---------------------------|-----|
| LAN - display | No |
| LAN - wireless networking | No |
| LAN | Yes |

Weight and dimensions

| | |
|------------------------|--------------------|
| Dimensions (W x D x H) | 25.6" x 28" x 9.8" |
|------------------------|--------------------|

| | |
|------------|-----------|
| Net weight | 110.2 lbs |
|------------|-----------|

| | |
|-----|-----------------|
| UPC | 796435 44 553 9 |
|-----|-----------------|

