

# 1080p Professional Installation Laser Projector

ZH606-W



## Bright, compact and virtually maintenance-free



- Bright 6,000 ANSI lumens and 1080p resolution
- 4K UHD HDR input with HDMI 2.0 (HDCP 2.2)
- DuraCore maintenance-free laser light source up to 30,000 hours
- Vertical lens shift with four corner correction and color matching
- LAN and RS232 control with Crestron, Extron, AMX and Telnet compatibility
- 360° and portrait mode operation

PRO|SCENE



Brighten any room with 6,000 lumen, 1080p projection with the remarkable Optoma ProScene ZH606. A laser light source eliminates lamp and filter replacements for up to 30,000 hours of low-cost and virtually maintenance-free operation.

Its compact size, low weight and quiet operation make it perfect for boardrooms, higher education, houses of worship and entertainment venues. Vertical lens shift, four corner correction, 360° and portrait mode operation enable flexible installations.

A variety of inputs, including HDMI and VGA, provide connectivity to high-quality 4K HDR digital video or legacy analog video sources while LAN and RS-232 enable control via Crestron, Extron, AMX, Telnet. Stereo speakers with 10W per channel provide rich audio for all-in-one applications, a 12V trigger output ensures compatibility with motorized screens.

## CONNECTIVITY (May require optional accessories)



Computers



Smart Phones



Tablets



3D Blu-ray/DVD Players



Camcorders



Apple TV®



Chromecast™

# 1080p Professional Installation Laser Projector - ZH606-W

## OPTICAL/TECHNICAL SPECIFICATIONS

<b>Display Technology</b>	Texas Instruments™ 0.65" 1080p DMD
<b>Color Wheel</b>	4 segment RGBY
<b>Native Resolution</b>	1080p
<b>Maximum Resolution</b>	4K (4096 x 2160, 60Hz)
<b>Brightness</b>	6,000 ANSI lumens
<b>Contrast Ratio</b>	300,000:1 (Extreme Black enabled) 1,800:1 full on/full off
<b>Displayable Colors</b>	1.07 billion
<b>Lamp Life and Type*</b>	Up to 30,000 hrs (Eco), 20,000 hrs (Normal)
<b>Light Source Type*</b>	DuraCore Laser
<b>Projection Method</b>	360°, front, rear, ceiling mount, table top
<b>Keystone Correction</b>	±30° horizontal and vertical
<b>Geometry</b>	Four corner adjustment
<b>Lens Shift</b>	21% vertical
<b>Uniformity</b>	85%
<b>Offset</b>	106%
<b>Aspect Ratio</b>	16:9 (native), 4:3 compatible
<b>Throw Ratio</b>	1.2-1.9:1
<b>Projection Distance</b>	4.3' - 32.8
<b>Image Size</b>	31" – 301"
<b>Projection Lens</b>	F=2.5-3.0 f=17.63-31.63
<b>Optical Zoom</b>	1.6x
<b>Digital Zoom</b>	0.8 - 2.0x
<b>Audio</b>	2 x 10W (stereo)
<b>Noise Level</b>	32db
<b>Remote Control</b>	Full size remote with laser pointer
<b>360° and Portrait mode operation†</b>	Yes (limitations apply on 360° single axis installation. Please check user manual for more details)
<b>Operating Temperature</b>	41–104°F (5–40°C), 85% max humidity
<b>Power Supply</b>	AC input 100–240V, 50–60Hz, auto-switching
<b>Power Consumption</b>	Bright: 415W (typical), 477W (max) Eco: 182W (typical), 209W (max)
<b>High Altitude</b>	Operating temperature at sea level up to 10,000 feet = 104° F (max); Must manually switch to high altitude mode from 5,000 feet and above (using OSD menu) to maintain optimal functionality.

## COMPATIBILITY SPECIFICATIONS

<b>Computer Compatibility</b>	VGA, SVGA, HDTV(720P), WXGA, WXGA+, SXGA, SXGA+, UXGA, HDTV(1080p), WUXGA, 4K UHD (24/30/50/60Hz), 4K (DCI) (24/30Hz)
<b>Video Input Compatibility</b>	PAL, SECAM, 576i/p, NTSC, 480i/p, HDTV 720p/1080i/1080p 4K UHD 2160p (24/30/50/60 Hz), 4K (DCI) (24/30Hz)
<b>3D Compatibility†</b>	Supports all HDMI 1.4a mandatory 3D formats (Frame pack, side-by-side, top-bottom) and up converts frame rate from 60Hz to 120Hz or 24Hz to 144Hz (i.e. 60 or 72 frames per eye). 3D glasses are needed and are sold separately. Refer to user manual for details.
<b>Vertical Scan Rate</b>	24 ~ 85 Hz (120Hz for 3D feature projector)
<b>Horizontal Scan Rate</b>	15.375 ~ 91.146 KHz
<b>User Controls</b>	Graphic user interface and on-screen menu in 27 languages
<b>I/O Connection Ports</b>	1x HDMI 2.0 (HDCP 2.2, MHL), 1x HDMI 1.4, 1x composite, 1x VGA, 1x composite, 1x VGA out, 1x audio in, 1x mic/audio in, 1x USB-A (power), 1x 12V trigger
<b>Control</b>	1x RJ-45, 1x RS-232C
<b>Loop Through (Audio)</b>	No


## PHYSICAL SPECIFICATIONS

<b>Security</b>	Kensington® lock port, password (OSD)
<b>Weight</b>	12.3 lbs
<b>Dimensions (W x H x D)</b>	14.7" x 4.6" x 11.9"

\*Light source life is dependent on brightness mode, display mode, usage, environmental conditions and more. Light source brightness can decrease over time.

†Watching 3D projection while wearing 3D glasses for an extended period of time may cause headaches or fatigue. If you experience a headache, fatigue or dizziness, stop viewing the 3D projection and rest.

‡Portrait orientation must follow the recommended positions. Please consult the user manual for further information.



### Warranty

3-year or 20,000 hour light source warranty (whichever comes first), 3-year Optoma Express advance exchange warranty on the projector.

### What's in the Box

ZH606-W, AC power cable, remote, batteries, quick start guide and warranty card

### Optional Accessories

Remote, mount

### Accessory Part Numbers

Universal ceiling mount: BM-5001U  
Remote: BR-3075W

UPC 796435 44 454 9

Optoma.com



Copyright © 2019 Optoma Technology, Inc. DLP® and the DLP logo are registered trademarks of Texas Instruments™. All other trademarks are the property of their respective owners. All specifications subject to change at any time. 09182019