

P5278P

PATIO BLASTER P SERIES SPEAKERS



P5278P

- 70 Volt System
- 5", 2-Way, Ported
- 40 Watts RMS Maximum Power
- 2.5, 5, 10, 20 Watts Taps
- Dispersion 120°
- Outdoor/Indoor
- Weatherized Aluminum Grill and Bracket
- Black and White Colors Available
- "U" Mount Bracket Included
- Ceiling or Wall Mount Possibilities
- 6", 8" Available.

P5278P

ARCHITECTS AND ENGINEERS
SPECIFICATIONS/TECHNICAL DATA

PATIO BLASTER P SERIES



GENERAL SPECIFICATIONS:

MODEL NUMBER:	P5278P
DESCRIPTION:	5", 2-Way, ported
OUTDOOR:	YES
IMPEDANCE:	70 Volt
DISPERSION:	120°
SENSITIVITY (1W/1M):	87 dB +/- 3dB
MAX POWER:	40 Watts
NOMINAL POWER:	2.5, 5, 10, 20 Watts
FREQUENCY RESPONSE:	75 Hz - 20 kHz
CROSS OVER:	4 kHz
HIGH FREQUENCY DRIVER:	3/4", Dome
LOW FREQUENCY DRIVER:	5", Polypropylene/Rubber
WOOFER SIZE:	5"
WOOFER MATERIAL:	Polypropylene/Rubber
TWEETER/S:	1 Each
TWEETER SIZE:	3/4"
TWEETER MATERIAL:	Poly carbonate
GRILL MATERIAL:	Aluminum
ENCLOSURE:	Plastic
DIMENSIONS: (LxWxH/inches):	7 ^{2/8"} x 7 ^{1/8"} x 9 ^{6/8"}
WEIGHT (pounds):	5.25 Lbs.
COLOR/S:	Black, White
PAINTABLE:	YES

ACCESSORIES:

• SS-36	In Ground Stainless Steel Stake (36")
• OWI1070M	Attenuator, Mono, 70V, 10W Max
• OWI3570M	Attenuator, Mono, 70V, 35W Max
• OWI7570M	Attenuator, Mono, 70V, 75W Max
• OWI2570S	Attenuator, Stereo, 70V, 25W Max



Touchboards

205 Westwood Ave, Long Branch, NJ 07740
Phone: 866-94 BOARDS (26273) / (732)-222-1511
Fax: (732)-222-7088 | E-mail: sales@touchboards.com