ĒNO® PROJECTOR KIT SPECIFICATIONS

Projector and mount solution for the ēno interactive whiteboard.



STEELCASE PJ930 PROJECTOR

<u></u>	11100201011
Panel Size / resolution	0.65" WXGA, S450, DDP4421
Technology	DLP
Throw ratio	Ultra short throw 0.35
Lumens	3000 (standard) 2450 (eco)
Contrast ratio	2300:1
Resolution	WXGA, XGA
Aspect ratios	16:10 (Native) 4:3 16:9
Lamp life	5,000 hours (standard) 8,000 hours (eco)
Power button	Yes
3D Ready	Yes
Speaker(s)	10W (two speakers)
Color wheel	6 segment (RGBCYW)
Noise level	33dB (standard) 29dB (eco)
Power supply	AC input 100~240 +/- 10% voltage
Power consumption	290W (standard) 260W (eco) <0.5W (standby)

LED Indicator	Power LED: Green Temp LED: Red Lamp LED: Amber
Input signal	Data: VESA Standard HDTV: 1080i / 720p / 1080p DTV: 4801i / 480p Video: NTSC/NTSC 4.43 PAL B/G/H/I, SECAM
Terminal I/O	Computer in: VGA (2), Display Port Computer out: VGA Video in: Video, S-Video, HDMI (1.4) Audio in: Mini jack, RCA R/L Audio out: Mini jack Microphone: Phone jack
Control I/O	Network management: RJ45 USB (upgrades) Room control: RS232
Temperature	Non-operating: -10 ~ 60 degree C Operating: 5 ~ 40 degree C
Altitude	Non-operating: Sea level ~ 30,000 FT Operating: Sea level ~ 10,000 FT @23 degree C
Humidity	Non-operating: 5% ~ 95% (no condensation) Operating: 10% ~ 85% (no condensation)
Accessories	Power cord: 4.5m VGA cable: 4.5m Remote control User Manual (CD)
Lamp replacement	While mounted Part No. 23354001SR
Remote control replacement	Part No. 23354101SR
Kensington Lock Slot	Yes
Warranty	3 year - Warranty excludes products considered by Steelcase to be consumables (e.g., batteries, lamps, except projector lamps offer 6 months coverage)
Dimensions	Device: 11.3" x 14.7" x 4.9" (288 x 375 x 126 mm) 11 lb (5 kg) Shipping: 11" x 20" x 17" (279 x 508 x 432 mm) 17.6 lb (8 kg)





PEERLESS PSTA600 MOUNT

Fully integrated cable management systems conceals and protects cables for a clean finish

Model number	Peerless PSTA-600
Finish	Aluminum alloy, powder coat
Weight	8.5 lbs (3.8kg)
Max load	25 lbs (11.3 kg)
Certifications	UL listed (US and Canada) for masonry and wood-studded walls
Warranty	Limited 5 year warranty
Dimensions	Mount: 25.0" x 9.6" x 10.6" (635 x 244 x 271mm) Shipping: 21.0" x 12.0" x 11.0" (533 x 305 x 279 mm) 10.5 lb (4.7 kg)
Package Contents	Ultra short throw arm, end cap, PSRGS-UNV, installation hardware, assembly instructions

