

PJT155R - Single Touch Monitor



Specification

Product Name
 Planar Part Number
 Viewable Size
 Touchscreen Type
 Number of Touch Points
 Touchscreen Interface
 Transmissivity
 Contrast Ratio (typ)
 Viewing Angle (typ)
 Response Time (typ)
 Brightness (w/touchscreen)
 Brightness (w/o touchscreen)
 Brightness (Typical)
 Display Type
 Display Resolution
 Aspect Ratio
 Tilt Range
 Palette
 Pixel Pitch
 Refresh Rate
 Panel Depth
 Dimensions (W x H x D)
 Dimensions without Stand
 Display Weight
 Display Weight (w/o stand)

Detail

PJT155R
 997-6376-00
 15" diagonal (11.97" x 8.98")
 5-wire Resistive
 1
 USB
 N/A
 500:1
 140° Horizontal and 130° Vertical
 8 ms
 200 cd/m²
 250 cd/m²
 N/A
 LCD Active Matrix Flat Panel Display (TFT)
 1024 x 768
 4:3
 -5° to +90°
 16.7 million colors
 0.297 mm
 56 to 75 Hz
 N/A
 13.2" x 13.4" x 7.8" (335.0 mm x 343.6 mm x 227.2 mm)
 13.2" x 11.7" x 2.4" (335.0 mm x 296.0 mm x 60.8 mm)
 9.9 lbs (4.5 kg)
 N/A

Shipping weight	13 lbs (5.9 kg)
Video Inputs	Analog
Audio Output	2 speakers, 1W/channel
Compatibility	Windows® 7, Vista, XP, 2000, ME, 98, NT 4.0, CE, XP Embedded, Linux, HID Compliant - no drivers needed for basic touchscreen operation
External Connections	D-sub 15-pin, Type B socket USB, Audio In, AC power-in
Power Supply	Internal
Power Requirements	100-240 VAC (50/60 Hz)
Power Consumption	25W
Operating Temperature	N/A
VESA Compatible/Location	Built-in 75 mm VESA, back of monitor
Service and Support	1-Year Customer First™ warranty featuring FREE 2-Day Advance Replacement (US only)
Options / Features	N/A
Product Approvals	UL/cUL, FCC-B, CB, RoHS
CI-Black-PN	997-6376-00
CI-White-PN	N/A
In the Box	PJT155R 15" Touchscreen LCD Monitor, Power Cord, VGA Cable, USB Cable (A to B), Audio-in Cable, User's Guide
UPC	8 10689 06376 6