

Supplement

Title: PLS4 Operators Supplement Issue: 1
Part Number: 4790200 Issue Date: 3/17
Print Date: Aug. 2016 Page Count: 2
Revision/Date:

This supplement contains information necessary to ensure the accuracy of the above Manual.



Change #1, 600

Replace the entire **Specifications** with:

Light source:	Semiconductor laser diode 635-670 nm, visible
Working range:	±100 feet (outdoor w/detector)
Accuracy:	±1/8" @ 30' (<3 mm @ 10 m) As tested: @ 70 °F (± 2°) @ 35 % (±5 %) relative humidity
Leveling:	Automatic
Leveling range	±6°
Power supply:	3AA batteries alkaline or rechargeable
Operating time:	+25 hours continuous use with single beam; 12.5 hours both beams
Operating temp:	0 °F to 122 °F (-18 °C to +50 °C)
Storage temp:	-5 °F to +140 °F (-20 °C to +60 °C)

Supplement

PLS4 Operators

Indicator:	Green light: ON Red light: EXCEEDS TILT/ TILT OVERRIDE #4 Amber light: BATTERY LOW Flashing: pulse beam-lines
Environment:	Water resistant; not submersible
Dimensions:	2" x 2-1/4" x 4-3/8"
Weight:	16 oz.(0.45kg) (including batteries)
Laser Power:	Class II