

PNU423, PNU473 & PNU553 Multi-Touch Series

- 32, 12 and 6 Point Simultaneous Multi-Touch
- High Brightness
- 24/7 Operation Performance
- Thin LED ADA Compliant Design
- Ultra-Smooth Glass, 12x Smoother
- Advanced Palm Rejection
- Impact Resistant, UL® 60950 § 4.2.5 Glass

High Brightness, 24/7 performance multi-touch systems based on the new SHARP PN-U displays. Available with 3 levels of multi-touch, including 32 point, 12 point and 6 point options.

Ultra-smooth touch surface with impact resistant, UL® 60950 § 4.2.5 glass advanced palm rejection delivers the highest level of touch experience.

The new LED Back Light panel affords a less than 3" front to back depth, exceeding ADA installation requirements.



Available as a precision engineered touch overlay accessory or completed touch display.¹

PN-U Series Display Size	SHARP® Model	PNU423	PNU473	PNU553
		42	47	55
	Panel Technology	60Hz (LED Edge Light)	60Hz (LED Edge Light)	120Hz (LED Edge Light)
	Resolution	1920 x 1080	1920 x 1080	1920 x 1080
	Brightness	500 cd/m ²	700 cd/m ²	700 cd/m ²
Active Screen Area	Inches	36-5/8" x 20-19/32"	40-15/16" x 23"	47-5/8" x 26-25/32"
	Metric	930.275mm x 508.594mm	1016.938mm x 584.200mm	1209.68mm x 680.244mm
Connectivity	Inputs	VGA, DVI, HDMI DP1.1, Component & Composite BNC, RS232C	VGA, DVI, HDMI DP1.1, Component & Composite BNC, RS232C	VGA, DVI, HDMI DP1.1, Component & Composite BNC, RS232C
	Outputs	DVI (Loop), Stereo Mini Jack, RJ45, RS232C	DVI (Loop), Stereo Mini Jack, RJ45, RS232C	DVI (Loop), Stereo Mini Jack, RJ45, RS232C
	Audio	Built-in Speaker (10W + 10W) RCA pin (L/R) In/Out	Built-in Speaker (10W + 10W) RCA pin (L/R) In/Out	Built-in Speaker (10W + 10W) RCA pin (L/R) In/Out
	Tuner	N/A	N/A	N/A
	Media Player / CPU	External Options: PN-TPC2W7A	External Options: PN-TPC2W7A	External Options: PN-TPC2W7A
Multi-Touch Overlays: 6 Point Overlay Accessory 12 Point Overlay Accessory 32 Point Overlay Accessory Dimensions (Installed)	Order Part Number	4250-SOTA-6IR	4750-SOTA-6IR	5550-SOTA-6IR
	Order Part Number	4250-SOTA-12IR	4750-SOTA-12IR	5550-SOTA-12IR
	Order Part Number	4250-SOTA-32IR	4750-SOTA-32IR	5550-SOTA-32IR
	Inches	38.89" x 22.73" x 2.89"	42.88" x 24.90" x 2.83"	49.73" x 28.90" x 2.79"
	Metric	987.81mm x 577.34mm x 73.41mm	1089.52mm x 632.46mm x 71.88mm	1089.52mm x 632.46mm x 71.88mm

¹ Available as a precision engineered touch overlay accessory or completed touch display for U.S.A delivery. Outside the United States order as an overlay accessory.