

**POWER**  **WERSIDE**®

# **PQube® 3 Portable and Accessories**



## PQUBE 3 PORTABLE

The PQube 3 Portable combines the powerful monitoring and communication capabilities of the PQube 3 Power Analyzer with the quick install feature of a portable instrument. Designed for quick installation with Flexible CTs and fused voltage cables, it auto-detects frequency, nominal voltage and wiring configuration. The PQube 3 Portable can be used stand alone with a USB stick for configuration and data download. If connected to a network, it delivers event notifications and daily, weekly, as well as monthly reports directly.

### Description

- Easy to install, wire, and operate
- Self powers from the measured voltage (360 to 480Vac)
- Powers from 24 Vdc or with an external transformer 120 to 240 Vac
- 1 hour battery power backup
- Voltage range 100 to 480 Vac nominal.
- Current range (0 to 3000Amps)
- Power Quality Class A IEC 61000-4-30 Ed3\*
- Monitors AC and DC (4 additional analog inputs)
- Detects High-Frequency transients at 4MHz
- Records 2kHz to 150kHz conducted emissions
- Optional 2 environment probes (temperature, humidity, barometric pressure, acceleration)
- Comes with:
  - (4) flexible 3000A rated CTs, (1) 5A split-core CT
  - Fused voltage leads with alligator clips, Carrying case



### Order Part Number:

#### PQube 3 Portable

PQ3iaB-PORTABLE-NEO-000-0000-XXXX (PQube 3 Portable only)

PQ3iaB-PORTABLE-NEO-M24-0000-XXXX (PQube 3 Portable only, modem ready)

#### PQube 3 Portable with accessories kit

PQ3iaB-PORTABLE-4V8I-480V-000-XXXX (PQube3 Portable with kit)

PQ3iaB-PORTABLE-4V8I-480V-M24-XXXX (PQube3 Portable with kit, modem ready)



## FLEXIBLE CT - 3000A

Cable with Bayonet connector, 4 meter long. Loop length 24".

**Order Part Number:** FCT-24-3000A-BL-XX



## HIGH ACCURACY 5A RATED SPLIT-CORE

Current sensor with Bayonet connector for PQube 3 Portable. 1.25"x1.25" opening.

**Order Part Number:** SCN4-5A:333mV-1.25-BL



## REPLACEMENT POWER SUPPLY

Bayonet connector.  
100~240Vac input / 24Vdc output.

**Order Part Number:** Portable-PowerSupply-BL-0000-XX



## CT/FLEXIBLE ADAPTOR (BAYONET)

Wire+connector length is 4".

Order Part Number: [ADAPT-PQPORT-4.0-XX](#)



## REPLACEMENT BATTERY PACK

Provides up to 60min backup.

Order Part Number: [BATTPACK-6V-2.5AH-XB1-XX](#)



## REPLACEMENT VOLTAGE LEADS KIT

Order Part Number: [Voltage-Lead-Kit-0000-XX](#)



## EXTENSION CABLE FOR MODEM ANTENNA

Connects your remote SMA style cell antenna to the PQ3iaB-Portable package with cell modem ready option. 4 meter long. Antennas not included.

**Order Part Number:** [CABLE-CELL-SMA-SMA-04M-00](#)

## MOUNTING KIT FOR 2 SMA STYLE REMOTE ANTENNAS

Includes remote antenna mounting bracket and 2 SMA to SMA cables, 4 meter long. Application: remotely mounting two SMA type indoor cell antennas (not included).

**Order Part Number:** [RAK-PQ3IABP-SMA-4M-00](#)

## MAGNETIC MOUNTING KIT FOR REMOTE ANTENNAS

Magnetic Mounting Kit for Remote Antenna Bracket - use these 6 powerful Neodymium magnets to mount your Remote Antenna Bracket onto an electric panel enclosure, or any other indoor flat steel surface.

**Order Part Number:** [MAGKIT-RAB-00](#)





[powerside.com](http://powerside.com)

Powerside®, PQube®, and EnviroSensor® are trademarks of Power Survey Ltd. and Power Standards Lab.  
© 2020 Powerside. All rights reserved.

**P**  **WERSIDE**®