

**PS4660T**



**Specification**

Product Name  
 Planar Part Number  
 Viewable Size  
 Aspect Ratio  
 Display Resolution  
 Brightness (Typical)  
 Contrast Ratio (typ)  
 Response Time (typ)  
 Viewing Angle (typ)  
 External Connections  
 Power Requirements  
 Power Consumption  
 Service and Support/Warranty  
 Product Approvals  
 VESA Compatible/Location  
 Audio Input  
 Audio Output  
 Bezel Width  
 Cabinet Dimensions (W x H x D)  
 Display Control  
 Display Weight  
 Shipping weight  
 Display Type  
 Refresh Rate  
 Operating Temperature  
 Operating Temperature

**Detail**

PS4660T  
 997-7044-00  
 46" diagonal  
 16:9  
 FHD 1080p (1920 x 1080)  
 500 cd/m<sup>2</sup>  
 4000:1  
 6.5 ms  
 178°  
 DisplayPort, HDMI, VGA, DVI  
 100 - 240V; 50/60Hz  
 145W (max)  
 3-Year Customer First™ Warranty featuring FREE 2-Day Advance Replacement (US only)  
 FCC Class A, UL, CE  
 400 mm x 400 mm; 8 holes  
 PC Audio in (Jack)  
 R/L Line out (Jack)  
 0.7" (18mm)  
 41.6" x 24.1" x 2.5" (1057mm x 612mm x 64mm)  
 RS232in, IR, Keypad  
 67 lbs (31 kg)  
 78 lbs (35 kg)  
 Edge-Lit LED LCD  
 60 Hz  
 5-40°C (41 -104°F)  
 5-35°C (41 -95°F)

Palette	16.7 million colors
Pixel Pitch	0.2812mm
Orientation	Landscape/Portrait
Speakers	10W x 2 built-in
Touchscreen Type	Optical multi-touch
OS Compatibility	Windows 7, Vista, XP, Mac OSX and Linux
Features	On/off scheduling, TAA compliant
In the Box	PS4660T display, power cord, VGA cable, IR extender cable, remote control, and USB cable
UPC	8 10689 07044 3