



## PT1510MX-WH - Single Touch Monitor

Specification	Detail
Product Name	PT1510MX-WH
Planar Part Number	997-3394-00
Viewable Size	15" diagonal (11.97" horizontal x 8.98" vertical)
Touchscreen Type	5-wire resistive touchscreen
Number of Touch Points	1
Touchscreen Interface	Dual Serial and USB
Transmissivity	78% (typical)
Contrast Ratio (typ)	500:1
Viewing Angle (typ)	140° Horizontal and 125° Vertical
Response Time (typ)	8 ms
Brightness (w/touchscreen)	190 cd/m²
Brightness (w/o touchscreen)	250 cd/m <sup>2</sup>
Brightness (Typical)	N/A
Display Type	LCD Active Matrix Flat Panel Display (TFT)
Display Resolution	1024 x 768
Aspect Ratio	N/A
Tilt Range	-3° to +25°
Palette	16.7 million colors
Pixel Pitch	0.297 mm
Refresh Rate	56 to 75 Hz (60 Hz recommended)
Panel Depth	2.2"
Dimensions (W x H x D)	15.9" x 15.3" x 7.5" (403.9 mm x 388.6 mm x 190.5 mm)
Dimensions without Stand	15.9" x 12.3" x 2.2" (403.9 mm x 312.4 mm x 55.9 mm)
Display Weight	10.4 lbs (4.7 kg)
Display Weight (w/o stand)	7.9 lbs (3.6 kg)
Shipping weight	16 lbs (7.3 kg)
Video Inputs	Analog
Audio Output	Integrated stereo speakers with 1W/channel
Compatibility	Windows® 7, Vista, XP, 2000, ME, 98, NT 4.0, CE, XP Embedded, Apple® Mac OS, Linux, HID Compliant - no drivers needed for basic touchscreen operation
External Connections	DC power-in barrel connector, D-sub 15 pin, Audio In connector, USB connector

Power Supply	External
Power Requirements	100-240 VAC, 50/60Hz
Power Consumption	30W (5W standby)
Operating Temperature	+5° to +35° C
VESA Compatible/Location	Built-in 75 mm VESA, monitor back
Service and Support	3-Year Customer First™ Warranty featuring FREE 2- Day Advance Replacement (US only)
Options / Features	Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® security lock function, Built-in 75 mm VESA, back
Product Approvals	UL/cUL, FCC-B, CE-B, TUV, RoHS, CCC, China RoHS
CI-Black-PN	997-3198-00
CI-White-PN	997-3394-00
In the Box	PT1510MX 15" Touchscreen LCD Monitor, Power Adapter, Power Cord, VGA Cable, RS-232 Cable, USB Cable (A to B), Audio-in Cable, Driver CD, User's Guide, Quick Start Guide
UPC	8 10689 03394 3



205 Westwood Ave, Long Branch, NJ 07740 Phone: 866-94 BOARDS (26273) / (732)-222-1511 Fax: (732)-222-7088 | E-mail: sales@touchboards.com