

PT1575S - Single Touch Monitor



Specification

Product Name	PT1575S
Planar Part Number	997-3406-00
Viewable Size	15" diagonal (11.97" horizontal x 8.98" vertical)
Touchscreen Type	SAW (Surface Acoustic Wave)
Number of Touch Points	1
Touchscreen Interface	Dual Serial/USB
Transmissivity	N/A
Contrast Ratio (typ)	500:1
Viewing Angle (typ)	140° H, 125° V
Response Time (typ)	8 ms
Brightness (w/touchscreen)	230 cd/m ²
Brightness (w/o touchscreen)	250 cd/m ²
Brightness (Typical)	N/A
Display Type	LCD Active Matrix Flat Panel Display (TFT)
Display Resolution	1024 x 768
Aspect Ratio	N/A
Tilt Range	-5° to 90°
Palette	16.7 million colors
Pixel Pitch	0.297 mm
Refresh Rate	56 to 75 Hz
Panel Depth	2.4"
Dimensions (W x H x D)	14.3" x 12.6" x 8.1" (364.0 mm x 321.4 mm x 206.1 mm)
Dimensions without Stand	14.3" x 11.6" x 2.4" (364.0 mm x 295.0 mm x 61.5 mm)
Display Weight	12.5 lbs (5.7 kg)
Display Weight (w/o stand)	9.5 lbs (4.3 kg)

Detail

Shipping weight	19 lbs (8.6 kg)
Video Inputs	Analog
Audio Output	2 speakers, 1W/ch
Compatibility	Windows® 7, Vista, XP, 2000, ME, 98, NT 4.0, CE, XP Embedded, Apple® Mac OS, Linux, HID Compliant - no drivers needed for basic touchscreen operation
External Connections	D-sub 15-pin, D-sub 9-pin, Type B socket USB, Stereo Jack - 3mm, AC Power-in, DC Power-in
Power Supply	Internal AC power supply, 12V DC power connector (Optional DC power supply may be sourced separately)
Power Requirements	100-240 VAC, 50/60 Hz
Power Consumption	25W (4W standby)
Operating Temperature	0° to +40° C
VESA Compatible/Location	Built-in 75 mm VESA, monitor back
Service and Support	3-Year Customer First™ Warranty featuring FREE 2-Day Advance Replacement (US only)
Options / Features	Anti-glare coating, Multi-language support, On screen display (OSD)
Product Approvals	UL/c-UL, FCC-Class B, CE, RoHS
CI-Black-PN	997-3406-00
CI-White-PN	N/A
In the Box	PT1575S 15" Touchscreen LCD Monitor, Power Cord, VGA Cable, RS-232 Cable, USB Cable (A to B), Audio-in Cable, Driver CD, User's Guide, Quick Start Guide
UPC	8 10689 03406 3