

PT1585P - Dual Touch Monitor



Specification

Product Name	PT1585P
Planar Part Number	997-6313-00
Viewable Size	15" diagonal (11.97" horizontal x 8.98" vertical)
Touchscreen Type	Projected Capacitive
Number of Touch Points	2
Touchscreen Interface	USB
Transmissivity	N/A
Contrast Ratio (typ)	500:1
Viewing Angle (typ)	140° Horizontal and 125° Vertical
Response Time (typ)	8 ms
Brightness (w/touchscreen)	225 cd/m ²
Brightness (w/o touchscreen)	250 cd/m ²
Brightness (Typical)	N/A
Display Type	LCD Active Matrix Flat Panel Display (TFT)
Display Resolution	1024 x 768
Aspect Ratio	N/A
Tilt Range	-5° to 90°
Palette	N/A
Pixel Pitch	0.297 mm
Refresh Rate	31 to 60.2 Hz
Panel Depth	N/A
Dimensions (W x H x D)	14.3" x 12.7" x 8.1" (364.4 mm x 322.1 mm x 206.2 mm)
Dimensions without Stand	14.3" x 11.6" x 2.7" (364.4 mm x 295.4 mm x 67.4 mm)
Display Weight	12.2 lbs (5.5 kg)
Display Weight (w/o stand)	8.7 lbs (3.9 kg)

Detail

Shipping weight	18 lbs (8.2 kg)
Video Inputs	Analog
Audio Output	2 speakers, 1W/channel
Compatibility	Windows® 7, Vista, XP, 2000, XP Embedded, Linux, Apple® Mac OS, HID Compliant - no drivers needed for basic touchscreen operation
External Connections	D-sub 15-pin, Type B socket USB, Stereo jack - 3 mm, AC power-in, DC power connector
Power Supply	Internal
Power Requirements	AC 100-240 VAC, 50-60 Hz
Power Consumption	22W (3W sleep, 1W off)
Operating Temperature	0° to +40° C
VESA Compatible/Location	Built-in 75 mm VESA, back
Service and Support	3-Year Customer First™ Warranty featuring FREE 2-Day Advance Replacement (US only)
Options / Features	N/A
Product Approvals	UL/c-UL, FCC-Class B, CE, RoHS
CI-Black-PN	997-6313-00
CI-White-PN	N/A
In the Box	PT1585P 15" Touchscreen LCD Monitor, Power Cord, VGA Cable, USB Cable (A to B), Audio-in Cable, Driver CD, User's Guide, Quick Start Guide
UPC	8 10689 06313 1