

PRG-EXA(-S)(-W)
 PRG-EXB(-S)(-W)
 PRG-EXC(-S)(-W)

PRG Series Adjustable Projector Ceiling/Wall Mount Kit

For Multimedia Projectors up to 50 lb (22 kg)

Peerless has packaged flexibility and ease together in one box with these ceiling/wall mounting kits, which enable the installation of a projector from either the ceiling or the wall. This all-in-one kit includes the industry's first precision gear projector mount that delivers precision image alignment with a simple turn of a knob. These comprehensive projector mounting kits also include an adjustable length column that provides ideal height positioning for the perfect projector installation. Concealed within the column is a cable-management channel, assuring a clean and clutter-free appearance.



Max load: 50 lb (22 kg)



FEATURES

- Continuous channel design for uninterrupted drop length or wall extension adjustments
- Three adjustable extension lengths:
 - PRG-EXA models: (ceiling/wall) 8.7"-12.8" (221-325 mm)
 - 9.72" -13.86" (247-352 mm)
 - PRG-EXB models: (ceiling/wall) 12.68"-20.67" (322-525 mm)
 - 13.74" - 21.73" (349-552 mm)
 - PRG-EXC models: (ceiling only) 19.13"-32.91" (486-836 mm)
- Safety catch designed into extension to ensure user and equipment safety
- Mounts to ceiling or wall (according to model) with included wall mount interface
- Spider® Universal Adapter Plate extends up to 17.63" (448 mm) to fit most projector models
- Internal cable management within channels for clean, clutter-free appearance
- Includes PRG Precision Gear Projector Mount that provides pin-point image alignment with the unique gearing system by simply adjusting two knobs
- Specifications:
 - Tilt: ±20°
 - Roll: ±10°
 - Swivel: 360°

■ **ACHIEVE IDEAL PLACEMENT**
 Continuous channel design for uninterrupted drop length or wall extension adjustments

■ **PIN-POINT IMAGE ALIGNMENT**
 Includes PRG Precision Gear Projector Mount that provides pin-point image alignment with its unique gearing system by simply adjusting two knobs

■ **ADDED PEACE-OF-MIND**
 Incorporates safety catch design into extension channels to ensure user and equipment safety

■ **UNIVERSAL COMPATIBILITY**
 Includes the Spider® Universal Adapter Plate which extends up to 17.63" (448 mm) to fit most projector models



Touchboards

205 Westwood Ave, Long Branch, NJ 07740
 Phone: 866-94 BOARDS (26273) / (732)-222-1511
 Fax: (732)-222-7088 | E-mail: sales@touchboards.com



Safety Catch Mechanism



Wall Adapter Included with PRG-EXA & PRG-EXB



Model Numbers

| | |
|-------------------------|--|
| PRG-EXA(-S)(-W): | PRG Series Adjustable Projector Ceiling/Wall Mount Kit |
| PRG-EXB(-S)(-W): | PRG Series Adjustable Projector Ceiling/Wall Mount Kit |
| PRG-EXC(-S)(-W): | PRG Series Adjustable Projector Ceiling Mount Kit |

Product Specifications

| | DIMENSIONS (W x H x D) with adapter plate | PRODUCT WEIGHT | LOAD CAPACITY | FINISH | AVAILABLE COLORS |
|------------------------|---|-----------------------|----------------------|-------------------------------|-------------------------|
| PRG-EXA(-S)(-W) | 8.5-17.63" x 8.7"-12.8" x 8.5-17.63" (216-448 x 221-325 x 216-448 mm) | 6.81 lb (3.09 kg) | 50 lb (22 kg) | Scratch resistant fused epoxy | PRG-EXA: Black |
| PRG-EXB(-S)(-W) | 8.5-17.63" x 12.68"-20.67" x 8.5-17.63" (216-448 x 322-525 x 216-448 mm) | 7.17 lb (3.25 kg) | | | PRG-EXA-S: Silver |
| PRG-EXC(-S)(-W) | 8.5-17.63" x 19.19"-32.91" x 8.5-17.63" (216-448 x 486-836 x 216-448 mm) | 7.95 lb (3.61 kg) | | | PRG-EXA-W: White |
| | | | | | PRG-EXB: Black |
| | | | | | PRG-EXB-S: Silver |
| | | | | | PRG-EXB-W: White |
| | | | | | PRG-EXC: Black |
| | | | | | PRG-EXC-S: Silver |
| | | | | | PRG-EXC-W: White |

Package Specifications

| | PACKAGE SIZE (W x H x D) | PACKAGE SHIP WEIGHT | PACKAGE UPC CODE | PACKAGE CONTENTS | UNITS IN PACKAGE |
|------------------------|--|----------------------------|---|--|-------------------------|
| PRG-EXA(-S)(-W) | 9.31" x 4.25" x 12.63" (237 x 108 x 321 mm) | 7.75 lb (3.52 kg) | PRG-EXA: 735029258476 PRG-EXA-S: 735029258483 PRG-EXA-W: 735029258483 | Wall/ceiling plate, adjustable extension columns, ceiling/wall connection brackets, PRG Precision Gear Projector Mount, Spider® Universal Adapter Plate, mounting and projector attachment hardware, assembly instructions | 1 |
| PRG-EXB(-S)(-W) | 9.31" x 4.25" x 12.63" (237 x 108 x 321 mm) | 8.11 lb (3.68 kg) | PRG-EXB: 735029258506 PRG-EXB-S: 735029258513 PRG-EXB-W: 735029258520 | | |
| PRG-EXC(-S)(-W) | 10" x 4.38" x 19.38" (254 x 111 x 492 mm) | 9.28 lb (4.21 kg) | PRG-EXC: 735029258537 PRG-EXC-S: 735029258544 PRG-EXC-W: 735029258551 | Ceiling plate, adjustable extension column, ceiling connection bracket, PRG Precision Gear Projector Mount, Spider® Universal Adapter Plate, mounting and projector attachment hardware, assembly instructions | |

Accessories

ACC-EXC(S)(W): Extension Column

All dimensions = inch (mm)

| PRG-EXA, PRG-EXB, PRG-EXC HEIGHT | | |
|----------------------------------|-----------------|-----------------|
| RANGE X | MINIMUM | MAXIMUM |
| PRG-EXA | 1.23" (31 mm) | 2.23" (57 mm) |
| PRG-EXB | 1.23" (31 mm) | 2.23" (57 mm) |
| PRG-EXC | 1.23" (31 mm) | 2.23" (57 mm) |
| RANGE Y | MINIMUM | MAXIMUM |
| PRG-EXA | 8.7" (221 mm) | 12.8" (325 mm) |
| PRG-EXB | 12.68" (322 mm) | 20.67" (525 mm) |
| PRG-EXC | 19.13" (486 mm) | 32.91" (836 mm) |
| RANGE Z | MINIMUM | MAXIMUM |
| PRG-EXA | 9.72" (247 mm) | 13.86" (352 mm) |
| PRG-EXB | 13.74" (349 mm) | 21.73" (552 mm) |
| PRG-EXC | n/a | n/a |

FRONT VIEW (Dimensions: 6.5" [165 mm] width, 2.47" [63 mm] height)

SIDE VIEW (Dimensions: 6.5" [165 mm] width, Z length)

TOP VIEW OF ADAPTER PLATE (Dimensions: 4.79" [122 mm] width, 17.63" [448 mm] length)

SWIVEL (YAW) 360° (when attached to an extension column), ±15° (when flush mounted)

±20° PITCH

±10° ROLL

ARCHITECTS SPECIFICATIONS

The PRG-Precision Gear Projector Mount shall be a Peerless model PRG-EXA; PRG-EXB; PRG-EXC and shall be located where indicated on the plans. It shall feature Tilt: ±20°, Roll: ±10°, and Swivel: 360° (when attached to an extension column), ±15° swivel (when flush mounted), which enables the image to be perfectly aligned with the screen. It shall be constructed of aluminum alloy finished in black, white, or silver. Assembly and installation shall be done according to instructions provided by the manufacturer.