

KIP640/642/643/646/
647/648/649/655(-S)



Mounting Pattern
200 x 200 up to
400 x 600mm




Max Load
75lb
(34kg)

Wall Kiosk Enclosure

Fits 40", 42", 43", 46", 47", 48", 49" and 55" Displays up to 2" (50mm) Thick

Peerless-AV's Wall Kiosk Enclosure provides a sleek digital showcase for advertising, entertaining, interactive wayfinding, and much more. These innovative kiosk enclosures accommodate a wide variety of ultra-thin displays in either landscape (KIL models) or portrait (KIP models) orientation. Despite the slim, ADA-compliant 3.97" profile, the kiosk enclosure can easily house media players, fans and other electrical equipment needed to create an impressive digital solution. From hotels to casinos to movie theaters, Peerless-AV's Wall Kiosk Enclosures are ideal for applications that want to take the guest experience up a notch and differentiate their brand.

- Eight way tool-less adjustment to quickly position display in kiosk window for flush alignment
- VESA® 200 x 200 up to 400 x 600mm compatible
- Thermostat controlled circulation fans ensure proper airflow within the kiosk
- Low profile design extends 3.97" (101mm) away from the wall, which meets the Americans with Disabilities Act (ADA) certification requirements
- Hinged top frame offers easy access to the display and other internal components for easy maintenance and enhanced security
- Supports wide range of aesthetic options including glass/acrylic, multiple colors, vinyl wraps, etc. to best match environment or promote brand strategy
- Pre-assembled to simplify installation of the entire solution
- Custom sizes available for smaller and larger displays



Landscape models available



Pull out mount for easy installation of display



RoHS
COMPLIANT



TAA
COMPLIANT

Please visit peerless-av.com/en-us/patents for patent information.

✉ info@peerless-av.com

🌐 peerless-av.com

peerless-AV[®]
Driving Technology Through Innovation

Model Numbers

WARRANTY: 5 years on metal components, 1 year on electronic components

Portrait Models:

KIP640(-S) Wall Kiosk Enclosure fits 40" Displays up to 2" (50mm) Thick
KIP642(-S) Wall Kiosk Enclosure fits 42" Displays up to 2" (50mm) Thick
KIP643(-S) Wall Kiosk Enclosure fits 43" Displays up to 2" (50mm) Thick
KIP646(-S) Wall Kiosk Enclosure fits 46" Displays up to 2" (50mm) Thick

KIP647(-S) Wall Kiosk Enclosure fits 47" Displays up to 2" (50mm) Thick
KIP648(-S) Wall Kiosk Enclosure fits 48" Displays up to 2" (50mm) Thick
KIP649(-S) Wall Kiosk Enclosure fits 49" Displays up to 2" (50mm) Thick
KIP655(-S) Wall Kiosk Enclosure fits 55" Displays up to 2" (50mm) Thick

Product Specifications

	DIMENSIONS (W x H x D)	PRODUCT WEIGHT	LOAD CAPACITY	FINISH	AVAILABLE COLORS
KIP640/642/643(-S)	27.10" x 44.24" x 3.94" (688 x 1124 x 100mm)	62.6lb (28kg)	75lb (34kg)	Powder Coat	KIP640/642/643/646/647/648/649/655: Gloss black KIP640-S/642-S/643-S/646-S/647-S/648-S/649-S/655-S: Silver
KIP646/647/648(-S)	29.10" x 48.16" x 3.94" (739 x 1223 x 100mm)	67.8lb (30kg)			
KIP649/655(-S)	33.50" x 55.07" x 3.94" (861 x 1399 x 100mm)	79.5lb (36kg)			

Package Specifications

	PACKAGE SIZE (W x H x D)	PACKAGE SHIP WEIGHT	PACKAGE UPC CODE		PACKAGE CONTENTS	UNITS IN PACKAGE
KIP640/642/643(-S)	50.00" x 36.00" x 8.00" (1270 x 914 x 203mm)	85lb (39kg)	KIP640: 735029296874 KIP642: 735029297451 KIP643: 735029315735	KIP640-S: 735029296935 KIP642-S: 735029297468 KIP643-S: 735029315766	Kiosk with display mounting hardware	1
KIP646/647/648(-S)	54.00" x 39.00" x 8.00" (1371 x 990 x 203mm)	95lb (43kg)	KIP646: 735029296881 KIP647: 735029296898 KIP648: 735029307990	KIP646-S: 735029296942 KIP647-S: 735029296966 KIP648-S: 735029308003		
KIP649/655(-S)	62.00" x 43.00" x 8.00" (1574 x 1092 x 203mm)	105lb (48kg)	KIP649: 735029318712 KIP655: 735029308102	KIP649-S: 735029318798 KIP655-S: 735029309199		

Accessories


ACC415: 4-pack Metal Stud Fastener Kit
CL-SCG200: Screen Cleaning Gel
DEB-HD10: 32' (10m) High Speed HDMI® Cables with Ethernet
PVP1000-PL6: Surge Protector with Six Outlets



KioskBuilder™:

Build your own Integrated Kiosk @ kiosks.peerless-av.com including integration services, flat panel display, media player, content management software, power protection, thermal management, display protection, vinyl graphics, etc.

All dimensions = inch (mm)



MODEL NO.	DIMENSION "A"	DIMENSION "B"	DIMENSION "C"	DIMENSION "D"	DIMENSION "E"
KIP640	27.10" (688mm)	3.94" (100mm)	44.24" (1124mm)	19.67" (500mm)	34.97" (888mm)
KIP642	27.10" (688mm)	3.94" (100mm)	44.24" (1124mm)	20.65" (525mm)	36.72" (933mm)
KIP643	27.10" (688mm)	3.94" (100mm)	44.24" (1124mm)	21.13" (537mm)	37.59" (955mm)
KIP646	29.10" (739mm)	3.94" (100mm)	48.16" (1223mm)	22.61" (574mm)	40.20" (1021mm)
KIP647	29.10" (739mm)	3.94" (100mm)	48.16" (1223mm)	23.10" (587mm)	41.07" (1043mm)
KIP648	29.10" (739mm)	3.94" (100mm)	48.16" (1223mm)	23.59" (599mm)	41.94" (1065mm)
KIP649	33.50" (851mm)	3.94" (100mm)	55.07" (1399mm)	24.08" (611mm)	42.82" (1087mm)
KIP655	33.50" (851mm)	3.94" (100mm)	55.07" (1399mm)	27.03" (686mm)	48.05" (1220mm)

Architect Specifications

The Wall Kiosk Enclosure shall be a Peerless-AV model KIP640(-S), 642(-S), 643(-S), 646(-S), 647(-S), 648(-S), 649(S) or 655(-S) and shall be located where indicated on the plans. Assembly and installation shall be done according to instructions provided by the manufacturer.

Visit peerless-av.com to see the complete line of AV solutions from Peerless-AV, including outdoor displays, kiosks, digital audio, display mounts, projector mounts, carts/stands, and a full assortment of accessories.

Peerless-AV
 2300 White Oak Circle
 Aurora, IL 60502 USA
(800) 865-2112
(630) 375-5100
Fax: (800) 359-6500

Peerless-AV Europe
 Unit 3 Watford Interchange
 Colonial Way, Watford
 Herts, WD24 4WP
 United Kingdom
+44 (0) 1923 200100
Fax: +44 (0) 1923 200101

Peerless-AV Latin America
 Av. de las Industrias 413
 Parque Industrial Escobedo
 General Escobedo, N.L.,
 México, 66062
+52 (81) 8384-8300
Fax: +52 (81) 8384-8360

peerless-AV®
 Driving Technology Through Innovation

LIT-1630 rev.1