

SFX645(P)



 Display size
32"-60"

 Max load
100lb (45kg)

SMARTMOUNT **XT**

Universal Flat Wall Mount

FOR 32" TO 60" DISPLAYS

Limitless placement opportunities are delivered with speed and ease with both horizontal and vertical adjustment capability. Its slim, open wall plate architecture delivers flat panel display placement flexibility and cable management. This slim mount is the ultimate solution for secure, low-profile applications.

SFX645 delivers limitless placement opportunities with speed and ease, including horizontal and vertical adjustment for post-installation leveling.



Additional Features

- ☒ Open wall plate design allows for total wall access, increasing electrical and cable management options
- ☒ Up to 13" (330mm) of horizontal display adjustment for centering display on wall
- ☒ Up to 1" (25mm) of vertical adjustment on each universal display adaptor bracket for post-installation leveling and height adjustment fine-tuning
- ☒ Secure installation with theft resistant security screws (on security units)
- ☒ Easy-Glide™ design ensures that the display is securely attached to the wall plate
- ☒ Universal display adaptor brackets easily hook onto wall plate for fast installation
- ☒ Low-profile design holds display 1.21" (31mm) from the wall
- ☒ Fits displays with mounting hole patterns from 75 x 75mm (2.95"W x 2.95"H) to 452 x 405mm (17.79"W x 15.95"H)

■ POST-INSTALLATION ADJUSTMENT

±0.5" of vertical adjustment for post-installation leveling and height adjustment fine-tuning



■ VIEWING FLEXIBILITY


Up to 13" of horizontal adjustment for centering display on wall

■ EASY INSTALLATION

Universal display adaptor brackets easily hook onto wall plate for fast installation

■ SECURE INSTALLATION

Theft resistant screws on secure units



Patented. Design Patent No. D659,698. Utility Patent No. 8,348,212; 8,517,322.



INTEGRATED
PARTNER
PROGRAM

Contact your Peerless-AV sales representative for more information

Low-profile design holds display 1.21" (31mm) from the wall

SFX645	SmartMountXT™ Universal Flat Wall Mount for 32" to 60" Displays - security models
SFX645P	SmartMountXT™ Universal Flat Wall Mount for 32" to 60" Displays - standard models

Product Specifications

	DIMENSIONS (W x H x D)	PRODUCT WEIGHT	LOAD CAPACITY	FINISH	AVAILABLE COLORS
SFX645(P)	19.37" x 16.89" x 1.21" (492 x 429 x 31mm)	4.53lb (2.05kg)	100lb (45kg)	Powder coat	Black





Package Specifications

	PACKAGE SIZE (W x H x D)	PACKAGE SHIP WEIGHT	PACKAGE UPC CODE	PACKAGE CONTENTS	UNITS IN PACKAGE
SFX645(P)	10.125" x 3.5" x 21.125" (257 x 89 x 537mm)	6.5lb (2.95kg)	SFX645: 735029278870 SFX645P: 735029279341	Universal Flat Wall Mount, attachment hardware, installation instructions	1

Accessories

ACCXT302: SmartMountXT™ Video Conferencing Shelf accessory
 ACCXT400: In-Wall Cable and Power Management Accessory with AC Surge Suppressor

All dimensions = inch (mm)



Architect Specifications

The SmartmountXT™ Universal Flat Wall Mount shall be a Peerless-AV® model SFX645 or SFX645P and shall be located where indicated on the plans. Assembly and installation shall be done according to instructions provided by the manufacturer.

Visit peerless-av.com to see the complete line of AV solutions from Peerless-AV, including outdoor displays, wireless, kiosks, digital audio, display mounts, projector mounts, carts/stands, and a full assortment of accessories.

Peerless-AV
 2300 White Oak Circle
 Aurora, IL 60502 USA
(800) 865-2112
(630) 375-5100
Fax: (800) 359-6500

Peerless-AV Europe
 Unit 3 Watford Interchange
 Colonial Way, Watford
 Herts, WD24 4WP
 United Kingdom
+44 (0) 1923 200100
Fax: +44 (0) 1923 200101

Peerless-AV de México
 Ave de las Industrias 413
 Parque Industrial Escobedo
 Escobedo, N.L.,
 Mexico 66050
+52 (81) 8384-8300
Fax: +52 (81) 8384-8360

peerless-AV®