



# 1525

## Air

Pelican™ Air cases are the first in a series of remarkable innovations engineered by Pelican, the pioneers of protective cases. For over 40 years Pelican has designed and crafted the most influential protective cases in the world, and we're just getting started. With the launch of the Pelican™ Air line of cases, we're redefining the future of protection with a remarkable union of light and tough.

- Automatic Purge Valve - Keeps water and dust out while balancing air pressure
- Super-light proprietary HPX<sup>2</sup>™ Polymer
- Business card holder



## CONFIGURATIONS



**1525**  
Standard



**1525NF**  
No Foam



**1525WD**  
With Padded Dividers



**1525TP**  
With TrekPak Divider System



**1525WF**  
With Foam

## DIMENSIONS

<b>Interior (L x W x D)</b>	20.50 x 11.31" x 6.75 (52.1 x 28.7 x 17.1 cm)
<b>Exterior (L x W x D)</b>	21.96 x 13.97" x 7.49 (55.8 x 35.5 x 19 cm)
<b>Lid Depth</b>	2.00" (5.1 cm)
<b>Bottom Depth</b>	4.75" (12.1 cm)
<b>Total Depth</b>	6.75" (17.1 cm)
<b>Int Volume</b>	0.91 ft <sup>3</sup> (0.026 m <sup>3</sup> )

## MATERIALS

<b>Body</b>	Proprietary Polypropylene Blend
<b>Latch</b>	ABS
<b>O-Ring</b>	EPDM
<b>Purge Body</b>	ABS
<b>Purge Vent</b>	Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

## COLORS

 Black	 Yellow	 Silver	 Orange
---	--	--	--

## WEIGHT

<b>Weight With Foam</b>	7.13 lbs (3.2 kg)
<b>Weight Empty</b>	5.99 lbs (2.7 kg)
<b>Buoyancy</b>	57.90 lbs (26.3 kg)

---

**Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

# TEMPERATURE

*Document created on 05-03-19*

---

**Minimum Temperature** -60°F (-51.1 °C)

**Maximum Temperature** 160°F (71.1 °C)

# FOAM PROPERTIES

---

**Layer 1 (Lid)** 2.03" Convolute

**Layer 2 (Base)** 3.75" Pick N Pluck

**Layer 3 (Base)** 0.70" Pad

---

# ACCESSORIES

---