



1615

Air

Pelican™ Air cases are the first in a series of remarkable innovations engineered by Pelican, the pioneers of protective cases. For over 40 years Pelican has designed and crafted the most influential protective cases in the world, and we're just getting started. With the launch of the Pelican™ Air line of cases, we're redefining the future of protection with a remarkable union of light and tough.

- Automatic Purge Valve - Keeps water and dust out while balancing air pressure
- Retractable extension handle
- Super-light proprietary HPX2™ Polymer
- Business card holder
- Quiet rolling stainless-steel bearing wheels
- Maximum airline check-in size*
- * Check with your airline for exact measurement requirements.



CONFIGURATIONS



1615
Standard



1615NF
No Foam



1615WD
With Padded Dividers



1615TP
With TrekPak Divider System



1615WF
With Foam

DIMENSIONS

Interior (L x W x D)	29.59 x 15.50" x 9.38 (75.2 x 39.4 x 23.8 cm)
Exterior (L x W x D)	32.58 x 18.40" x 11.02 (82.8 x 46.7 x 28 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	7.38" (18.7 cm)
Total Depth	9.38" (23.8 cm)
Int Volume	2.49 ft ³ (0.071 m ³)

MATERIALS

Body	Proprietary Polypropylene Blend
Latch	ABS
O-Ring	EPDM
Purge Body	ABS
Purge Vent	Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

COLORS

-  Black
-  Yellow
-  Silver
-  Orange

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

sales@pelican.com • www.pelican.com

WEIGHT

Document created on 05-03-19

Weight With Foam	17.60 lbs (8 kg)
Weight Empty	14.06 lbs (6.4 kg)
Buoyancy	169.20 lbs (76.7 kg)

TEMPERATURE

Minimum Temperature	-60°F (-51.1 °C)
Maximum Temperature	160°F (71.1 °C)

FOAM PROPERTIES

Layer 1 (Lid)	2.03" Convolute
Layer 2 (Base)	2.94" Pick N Pluck
Layer 3 (Base)	2.94" Pick N Pluck
Layer 4 (Base)	1.44" Pad

OTHER

Wheels	2
---------------	---

ACCESSORIES
