

#### 1620

#### **Protector**

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the artic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- Strong polyurethane wheels with stainless steel bearings
- Watertight, crushproof, and dustproof
- 4 level Pick N Pluck<sup>™</sup> with convoluted lid foam
- Automatic Pressure Equalization Valve balances interior pressure, keeps water out
- Easy open Double Throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design strong, light weight
- · Retractable extension handle
- Stainless steel hardware and padlock protectors



## **CONFIGURATIONS**



1620 Standard



**1624**With Padded Dividers



1620NF No Foam



1620WF With Foam

## **DIMENSIONS**

Interior (L x W x D) 21.48 x 16.42" x 12.54 (54.6 x 41.7 x 31.9 cm) Exterior (L x W x D) 24.76 x 19.57" x 13.90 (62.9 x 49.7 x 35.3 cm)

 Lid Depth
 2.01" (5.1 cm)

 Bottom Depth
 10.53" (26.7 cm)

 Total Depth
 12.54" (31.9 cm)

 Int Volume
 2.56 ft³ (0.072 m³)

## **MATERIALS**

**Body** Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

#### **Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

Purge Vent 3 Micron Hydrophobiconom • www.pelican.com

## **COLORS**

Document created on 04-17-19

Black OD Green Desert Tan

## **WEIGHT**

 Weight With Foam
 24.62 lbs (11.2 kg)

 Weight Empty
 21.20 lbs (9.6 kg)

 Buoyancy
 149.91 lbs (68 kg)

 Master Pack Weight
 26.90 lbs (12.2 kg)

## **TEMPERATURE**

Minimum Temperature -40°F (-40 °C)

Maximum Temperature 210°F (98.9 °C)

## **CERTIFICATIONS**

IP67 MIL C-4150J Def Stan 81-41 STANAG 4280

# FOAM PROPERTIES

Layer 1 (Lid) 1.00" Convolute
Layer 2 (Base) 1.00" Pad

Layer 3 (Base)2.38" Pick N PluckLayer 4 (Base)2.38" Pick N PluckLayer 5 (Base)2.38" Pick N PluckLayer 6 (Base)2.38" Pick N Pluck

## **OTHER**

Wheels 2
Extendable Handle yes
Master Pack 1
Nameplate yes
Military yes

## **ACCESSORIES**