

1660

Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the artic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- 4 strong polyurethane wheels with stainless steel bearings
- · Large 2-person fold down handles
- · Watertight, crushproof, and dustproof
- 3 level Pick N Pluck[™] with convoluted lid foam
- Automatic Pressure Equalization Valve balances interior pressure, keeps water out
- Easy open Double Throw latches
- O-ring seal
- Open cell core with solid wall design strong, light weight
- · Retractable extension handle
- Stainless steel hardware and padlock protectors



CONFIGURATIONS



1660 Standard



1664With Padded Dividers



1660NF No Foam



1660WF With Foam

DIMENSIONS

Interior (L x W x D) 28.20 x 19.66" x 17.63 (71.6 x 49.9 x 44.8 cm) Exterior (L x W x D) 31.59 x 22.99" x 19.48 (80.2 x 58.4 x 49.5 cm)

 Lid Depth
 3.50" (8.9 cm)

 Bottom Depth
 14.14" (35.9 cm)

 Total Depth
 17.64" (44.8 cm)

 Int Volume
 5.66 ft³ (0.16 m³)

MATERIALS

Body Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

Purge Vent 3 Micron Hydrophdbi@Noni-Whovem • www.pelican.com

COLORS

Document created on 04-15-19

Black OD Green Desert Tan

WEIGHT

 Weight With Foam
 42.16 lbs (19.1 kg)

 Weight Empty
 34.16 lbs (15.5 kg)

 Buoyancy
 365.00 lbs (165.6 kg)

 Master Pack Weight
 49.00 lbs (22.2 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C)

Maximum Temperature 210°F (98.9 °C)

CERTIFICATIONS

IP67

Def Stan 81-41 STANAG 4280

FOAM PROPERTIES

Layer 1 (Lid) 3.00" Convolute

Layer 2 (Base) 1.00" Pad

 Layer 3 (Base)
 4.25" Pick N Pluck

 Layer 4 (Base)
 4.25" Pick N Pluck

 Layer 5 (Base)
 4.25" Pick N Pluck

OTHER

Wheels4Extendable HandleyesMaster Pack1NameplateyesReduced AreayesMilitaryyes

ACCESSORIES