



iM2075

Storm

The Pelican™ Storm Case™ has the same legendary DNA as our Pelican Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch. Guaranteed for life, the Pelican Storm case is made in the USA and engineered using the finest components.

- Guaranteed for life
- **Watertight, crushproof, and dustproof**
- Two Press & Pull Latches
- Two Padlockable Hasps
- Double-layered, Soft-grip Handle
- Vortex™ Valve
- Powerful Hinges
- Lightweight Strong HPX® Resin



CONFIGURATIONS



iM2075
Standard



iM2075-X0000
No Foam



iM2075-X0002
With Padded Dividers



iM2075-X0001
With Foam

DIMENSIONS

Interior (L x W x D)	9.50 x 7.50" x 7.25 (24.1 x 19.1 x 18.4 cm)
Exterior (L x W x D)	11.80 x 9.80" x 7.70 (30 x 24.9 x 19.6 cm)
Lid Depth	1.50" (3.8 cm)
Bottom Depth	5.75" (14.6 cm)
Total Depth	7.25" (18.4 cm)
Int Volume	0.3 ft ³ (0.008 m ³)

MATERIALS

Body	Injection Molded HPX™ high performance resin
Latch	Valox - Polybutylene Terephthalate (PBT)
Latch (Alt)	Xenoy - Polyester/Polycarbonate blend
O-Ring	EPDM
Pins	Stainless Steel
Pins (Alt)	Aluminum
Foam	1.3/1.35 polyester
Purge Body	Valox - Polybutylene Terephthalate (PBT)
Purge Body (Alt)	Xenoy - Polyester/Polycarbonate blend
Purge Vent	Gortex membrane

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

sales@pelican.com • www.pelican.com

COLORS

Document created on 04-12-19

■ Black

■ Yellow

■ OD Green

WEIGHT

Weight With Foam	3.70 lbs (1.7 kg)
Weight Empty	3.30 lbs (1.5 kg)
Buoyancy	18.20 lbs (8.3 kg)
Master Pack Weight	18.20 lbs (8.3 kg)

TEMPERATURE

Minimum Temperature	-20°F (-28.9 °C)
Maximum Temperature	140°F (60 °C)

CERTIFICATIONS

MIL-STD-810F
ATA 300
FED-STD-101C

FOAM PROPERTIES

Layer 1 (Lid)	1.12" Convolute
Layer 2 (Base)	0.63" Pad
Layer 3 (Base)	2.69" Pick N Pluck
Layer 4 (Base)	2.69" Pick N Pluck

OTHER

Master Pack	4
Military	yes

ACCESSORIES