



## iM3075

### Storm

Transport Case

The Pelican™ Storm Case™ has the same legendary DNA as our Pelican Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch.

Guaranteed for life, the Pelican Storm case is made in the USA and engineered using the finest components.

- Seven Press & Pull Latches
- Guaranteed For Life
- Two Padlockable Hasps
- Two Double-layered, Soft-grip Handles
- In-line Wheels
- Powerful Hinges
- O-ring seal
- Two stainless steel padlock protectors
- Specialized molded foam interior designed for Pump or Semi-automatic shotguns and accessories
- Retention Strap Instructions



## CONFIGURATIONS



**iM3075**  
Standard



**iM3075-X0000**  
No Foam



**iM3075-X0002**  
With Padded Dividers



**iM3075-X0001**  
With Foam

## DIMENSIONS

<b>Interior (L x W x D)</b>	29.80 x 20.80" x 17.80 (75.7 x 52.8 x 45.2 cm)
<b>Exterior (L x W x D)</b>	33.30 x 24.40" x 19.30 (84.6 x 62 x 49 cm)
<b>Lid Depth</b>	4.00" (10.2 cm)
<b>Bottom Depth</b>	13.75" (34.9 cm)
<b>Total Depth</b>	17.75" (45.1 cm)
<b>Int Volume</b>	6.38 ft <sup>3</sup> (0.181 m <sup>3</sup> )

## MATERIALS

<b>Body</b>	Injection Molded HPX™ high performance resin
<b>Latch</b>	Valox - Polybutylene Terephthalate (PBT)
<b>Latch (Alt)</b>	Xenoy - Polyester/Polycarbonate blend
<b>O-Ring</b>	EPDM
<b>Pins</b>	Stainless Steel
<b>Pins (Alt)</b>	Aluminum
<b>Foam</b>	1.3/1.35 polyester
<b>Purge Body</b>	Valox - Polybutylene Terephthalate (PBT)

## Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

**Purge Body (Alt)**

Xenoy - Polyester Polycarbonate [sales@pelican.com](mailto:sales@pelican.com) [www.pelican.com](http://www.pelican.com)

**Purge Vent**

Gortex membrane

*Document created on 04-08-19*

# COLORS

■ Black

■ OD Green

# WEIGHT

<b>Weight With Foam</b>	45.00 lbs (20.4 kg)
<b>Weight Empty</b>	31.50 lbs (14.3 kg)
<b>Buoyancy</b>	388.20 lbs (176.1 kg)
<b>Master Pack Weight</b>	37.00 lbs (16.8 kg)

# TEMPERATURE

<b>Minimum Temperature</b>	-20°F (-28.9 °C)
<b>Maximum Temperature</b>	140°F (60 °C)

# CERTIFICATIONS

MIL-STD-810F  
ATA 300  
FED-STD-101C

# FOAM PROPERTIES

<b>Layer 1 (Lid)</b>	3.88" Convolute
<b>Layer 2 (Base)</b>	1.08" Pad
<b>Layer 3 (Base)</b>	1.75" Pick N Pluck
<b>Layer 4 (Base)</b>	3.00" Pick N Pluck
<b>Layer 5 (Base)</b>	3.00" Pick N Pluck
<b>Layer 6 (Base)</b>	3.00" Pick N Pluck
<b>Layer 7 (Base)</b>	3.00" Pick N Pluck

# OTHER

<b>Extendable Handle</b>	yes
<b>Master Pack</b>	1
<b>Military</b>	yes

# ACCESSORIES