



# ASM 310, universal voltage




Similar Image

## ASM 310, universal voltage

- Oil free pumping system, roughing capacity 1.7 m<sup>3</sup>/h
- Ultralight, only 21 kg (46 lbs) and easy to move
- Large bright color touchscreen with graphics functionality
- Intuitive and customizable menu
- Integrated SD memory card for recording and downloading capacities

### Dimensions



Technical Data	ASM 310, universal voltage
Backing pump	with oil free backing pump
Backing pump capacity	1.7 m <sup>3</sup> /h   1 cfm   28.33 l/min
Connection flange (in)	DN 25 ISO-KF
Detectable gases	<sup>4</sup> He, <sup>3</sup> He, H <sub>2</sub>
Dimensions (L x W x H)	350 x 254 x 415 mm   13.78 x 10 x 16.34 inch
I/O interfaces	Standard 15 pins I/O
Interface: Connection, device side	Basic 15 pins I/O
Minimum detectable leakage rate for helium (sniffing leak detection)	1 · 10 <sup>-8</sup> Pa m <sup>3</sup> /s   7.5 · 10 <sup>-8</sup> Torr l/s
Minimum detectable leakage rate for helium (vacuum leak detection)	1 · 10 <sup>-7</sup> mbar l/s
Operating temperature	5 · 10 <sup>-13</sup> Pa m <sup>3</sup> /s
Power consumption max.	10-40 °C   50-104 °F   283-313 K
Pumping speed for He	300 W
Response time (sniffing leak detection)	1.1 l/s
Sound power	< 1 s
Sound pressure level	< 45 dB(A)
Start-up time (20°C) with calibration	< 45 dB(A)
Start-up time (20°C) without calibration	< 3.5 min
Supply	< 2 min
Test method	90 – 240 V, 50/60 Hz
User interface	Vacuum and sniffing leak detection
Weight	Graphic color touch screen (detachable)
	21 kg   46.3 lb

Order number	
ASM 310	BSAA0000MM9A

Accessories	
<b>Cables Connection cables</b>	
Connection cable for remote control, 10 meters	110881
Connection cable for remote control, 15 meters	110882
<b>Cables Mains cables / Power cords</b>	
Mains cable, 2.5 m, Switzerland	103718
Mains cable, 2.5 m, U.K.	104411
Mains cable, 2 m, Italy	104758
<b>Control Devices Remote controls</b>	
Remote control, leak rate in mbar l/s, legend in English	106688
Remote control, leak rate in Pa m <sup>3</sup> /s, legend in Japanese	106690
Remote control, leak rate in Pa m <sup>3</sup> /s, legend in English	108880
Remote control, leak rate in Torr l/s, legend in English	108881
Remote control RC 10, wired/wireless, for ASM and ASI leak detectors	124193
<b>Sniffing/Spraying Helium pistols/ spray guns</b>	
Helium spray gun "Elite", spray gun with additional accessories in a case	109951
Helium spray gun, standard	112535
<b>Sniffing/Spraying Sniffer probes</b>	
Sniffer probe, 5 m hose length and rigid 9 cm nozzle	SNC1E1T1
Sniffer probe, 10 m hose length, rigid 9 cm nozzle	SNC2E1T1
<b>Transport Transportation accessories</b>	
Trolley with two wheels	114820
Transport case to safeguard the ASM 310 against shipping damage	119594

## **VACUUM SOLUTIONS FROM A SINGLE SOURCE**

Pfeiffer Vacuum stands for innovative and custom vacuum solutions worldwide, technological perfection, competent advice and reliable service.

## **COMPLETE RANGE OF PRODUCTS**

From a single component to complex systems:

We are the only supplier of vacuum technology that provides a complete product portfolio.

## **COMPETENCE IN THEORY AND PRACTICE**

Benefit from our know-how and our portfolio of training opportunities!

We support you with your plant layout and provide first-class on-site service worldwide.

Are you looking for a  
perfect vacuum solution?  
Please contact us:

**Pfeiffer Vacuum GmbH**  
Headquarters · Germany  
T +49 6441 802-0  
info@pfeiffer-vacuum.de

[www.pfeiffer-vacuum.com](http://www.pfeiffer-vacuum.com)

All data subject to change without prior notice.

**PFEIFFER**  **VACUUM**