

# 900-358 Digital Motorized BRINELL Hardness Tester w/Auto Z-Axis



**Auto Z-Axis!**



21 Industrial Ave Upper Saddle River, NJ. 07458  
Tel: (201) 962-7373 Fax: (201) 962-8353  
[www.phase2plus.com](http://www.phase2plus.com)

- **Load Cell driven system provides precise control of test force application**
- **Direct digital reading**
- **Engineered to obtain highly sensitive and accurate readings**
- **Perfect for laboratories, workshops, tool rooms, inspection labs, etc.**
- **Measuring Range: 8-650HBW**

**Specification:**

- Innovative closed-loop technology. The tester incorporates the latest load cell technology. The test load is applied via a closed-loop control unit with a load cell, a DC motor and an electronic measurement and control unit. The result is highly accurate Brinell hardness measurements at all test loads up to 0.5%. The common load overshoot or undershoot as known from traditional dead weight or open-loop systems is eliminated. The absence of mechanical weights not only eliminates friction problems but also makes the equipment less sensitive to misalignments caused by vibrations.
- The gross weight of the tester is 50% less than the traditional dead weights type tester.
- Test load selection by keyboard and LCD screen.
- Fully automatic test cycles. The Brinell hardness Tester features a fully automatic test cycle, load application, holding, unloading is performed fully automatically. This greatly improves reproducibility of test results since operator influence is eliminated.
- Selectable dwell times by screen. The indenter, load, and other test information are shown clearly on the large LCD screen.
- The directions for 0.102F/D<sup>2</sup> ratios selecting according to the materials and hardness range can be showing on the screen.
- Equipped with a 20X optical microscope to measure the diameter of Brinell indentation.
- Brinell Hardness Calculator (BHC) make the hardness value calculation easier and convenient.



**Technical data:**

<b>Loads :</b> 3000kgf (29400N), 1500Kgf (14700N), 1000Kgf (9800N), 750Kgf(7355N),500Kgf (4900N), 250Kgf (2452N), 187.5Kgf (1839N), 125Kgf (1226N),100Kgf (980N), 62.5Kgf(612.9N)		
<b>Load dwell duration:</b> 2s~99s, can be set and stored		
<b>Tungsten Carbide Ball indenter:</b> 10mm, 5mm, 2.5mm		
<b>Measuring range:</b> 3.18HBW~ 58HBW		
<b>Magnification of the microscope:</b> 20X		
<b>Resolution capability of the microscope:</b> 0.005mm		
<b>Accuracy of Brinell Hardness Value:</b>		
<b>Hardness Range(HBW)</b>	<b>Error (%)</b>	<b>Repeatability(%)</b>
≤ 125	± 3.0	≤ 3.0
125 < HBW ≤ 225	± 2.5	≤ 2.5
> 225	± 2.0	≤ 2.0
<b>Max measurable height:</b> 230 mm		
<b>Max measurable depth:</b> 140 mm		
<b>Dimensions:</b> 530mm×260mm×750mm		
<b>Power supply:</b> 220/110 V, 50/60 Hz, 4A		
<b>Weight:</b> 110kg		



21 Industrial Ave Upper Saddle River, NJ. 07458  
 Tel: (201) 962-7373 Fax: (201) 962-8353  
 www.phase2plus.com