

# Smart DC Hipot Model 480-10E



## Testing Applications

Measures output voltage, leakage current, and insulation resistance.

- Output voltage up to 80 kV DC
- Leakage current up to 10 mA

The model 480-10E smart DC hipot is a cutting-edge dielectric test instrument designed with an emphasis on operator safety, versatility and ease of use. Complying with the most rigorous safety requirements, the system is divided into two modules, a control unit and a high voltage generation unit. Additional safety features include an emergency stop switch and a built-in sound alarm. Furthermore, the ability to fully remote control the instrument from an Android device — both to program the settings as well as to perform the tests — provides increased safety protection and greater comfort for the operator. A built-in microprocessor allows the user to adjust the output voltage, test duration, maximum leakage current and ramp slope, allowing for more complex tests to be carried out automatically.

## Safety and Design Features

- Remote control via Bluetooth
- Digital & bar graph reading
- “Pass-Fail” LED indicator
- Audible alarm
- Emergency Off pushbutton
- Adjustable parameters: voltage, maximum leakage current, ramp and test duration
- Self-detection of sparks
- Built-in memory
- USB interface
- IP54 protection (with lid closed)
- Complies with IEC 61010-1

- **Lightweight** and **ruggedly constructed** for years of field use
- **Remote control** via **Bluetooth** connection to **Android™** devices
- **Android** and **Windows software** included (optional **Labview driver** available)
- **Built-in** memory



## Specifications

<b>INPUT</b>	<b>Voltage/Current</b>	120 or 240 V, 960 VA
	<b>Frequency</b>	50/60 Hz
<b>DC OUTPUT</b>	<b>Voltage/Current</b>	0-80 kV, 10 mA
	<b>Ripple</b>	<2%
	<b>Polarity</b>	Negative output, positive ground
<b>TEST VOLTAGE</b>	<b>Resolution</b>	100 V between 10 kV and 80 kV 10 V up to 9.99 kV
	<b>Accuracy</b>	±(2% of nominal value ±2 digits) with 1 mA load
<b>LEAKAGE CURRENT MEASUREMENT</b>		Max. 10 mA
	<b>Resolution</b>	0.01 mA
	<b>Accuracy</b>	±(2% of nominal value ±2 digits)
<b>INSULATION RESISTANCE MEASUREMENT</b>		From 1 MΩ to 40 GΩ
	<b>Accuracy</b>	±10% of the measured value
<b>BUILT-IN TIMER</b>		Up to 20 minutes
<b>OPERATING TEMPERATURE</b>		23°F to 122°F (-5°C to 50°C)
<b>STORAGE TEMPERATURE</b>		-13°F to 158°F (-25°C to 70°C)
<b>HUMIDITY</b>		<95%, non-condensing
<b>DIMENSIONS &amp; WEIGHT</b>	<b>Controls</b>	17.5" L x 14.2" W x 7.5" H (450 x 360 x 190 mm) 15.43 lbs (7 kgs)
	<b>High Voltage Module</b>	17.5" L x 14.2" W x 7.5" H (450 x 360 x 190 mm) 15.65 lbs (7.1 kgs)
<b>ACCESSORIES included</b>		1 Interconnection cable (controller module), 9.84' (3 m)* 1 High voltage cable, 19.68' (6 m)* 1 Return cable HV, 19.68' (6 m)* 1 Protective grounding cable, 16.40' (5 m) 1 Power cable 1 USB cable 1 Carrying bag 1 User guide 1 Software  <i>*Different lengths available upon request.</i>



**PHENIX**  
**TECHNOLOGIES**

### WORLD HEADQUARTERS

**Phenix Technologies, Inc.**  
75 Speicher Drive  
Accident, MD 21520 USA  
Ph: +1.301.746.8118  
Fx: +1.301.895.5570  
Info@phenixtech.com

### BRANCH OFFICES

**Phenix Systems AG**  
Riehenstrasse 62A, 4058 Basel, Switzerland  
Ph: +41.61.383.2770, Info@phenixsystems.com

**Phenix Asia**  
Zhong Cheng Rd, Sec 1, No 177, 2F, Taipei 11148 Taiwan  
Ph: +886.2.2835.9738, Fx: +886.2.2835.9879, Info@phenixasia.com

ISO  
9001:2008  
Compliant

