

## LA1500RTR

### Specification

### Detail

Product Name	LA1500RTR
Planar Part Number	997-3468-01LF
Touchscreen Type	Gunze® 5-wire resistive
Touchscreen Interface	Dual Serial/USB
Compatibility	N/A
Brightness (Typical)	N/A
Brightness (w/touchscreen)	198 cd/m <sup>2</sup>
Brightness (w/o touchscreen)	250 cd/m <sup>2</sup>
Transmissivity	Up to 78%
Contrast Ratio (typ)	600:1
Response Time (typ)	8 ms
Horizontal Scan	31.5 ~ 60 KHz
Viewing Angle (typ)	155H, 155V
Pixel Pitch	0.297 mm
Refresh Rate	56 to 75 Hz
Video Inputs	Analog
Power Supply	External Module with IEC320 Connector, USA Cord-set, UL1950 certified
Power Requirements	100-240 VAC (50/60 Hz)
Power Consumption	30W (3W standby)
External Connections	D-sub 15 pin, Type B socket USB, D-sub 9 pin, RS232
Options / Features	Anti-glare coating, Multi-language support, On screen display (OSD)
Viewable Size	304 mm x 228 mm (15" diagonal)
Display Resolution	1024 x 768
Dimensions (W x H x D)	14.2" x 10.6" x 1.9" (360 mm x 270 mm x 47 mm)
Display Weight	9.2 lbs (4.2 kg) net; 13 lbs (5.9 kg) shipping
Shipping weight	N/A
Product Approvals	UL, FCC-B, CE-B, TUV, RoHS
Operating Temperature	+5° to +35° C
Service and Support/Warranty	3-Year Customer First™ Warranty featuring FREE 2-Day Advance Replacement (US only)
VESA Compatible/Location	Adjustable rear panel mounting brackets included, VESA 75 mm compatible
UPC	8 10689 03468 1

For more information, please visit [www.planar.com](http://www.planar.com)

*Specifications are subject to change without notice.*

*Specification Report Date: 6/20/2013*

*(c)Copyright 2013 Planar Systems, Inc. All rights reserved*