



When image experience matters.

LA1950RTR

Specification

Detail

Product Name	LA1950RTR
Planar Part Number	997-6288-00LF
Touchscreen Type	5-wire Resistive
Touchscreen Interface	Dual Serial/USB
Compatibility	Windows® 7, Vista, XP, 2000, ME, 98, NT 4.0, CE, XP Embedded, Apple® Mac OS, Linux, HID Compliant - no drivers needed for basic touchscreen operation
Brightness (Typical)	N/A
Brightness (w/touchscreen)	200 cd/m ²
Brightness (w/o touchscreen)	250 cd/m ²
Transmissivity	N/A
Contrast Ratio (typ)	800:1
Response Time (typ)	5 ms
Horizontal Scan	31.5 - 80 KHz
Viewing Angle (typ)	160° H,V
Pixel Pitch	0.294 mm
Refresh Rate	56 to 75 Hz
Video Inputs	Analog; 15-pin D-sub connector
Power Supply	External
Power Requirements	100-240 VAC (50/60 Hz)
Power Consumption	25W (<4W standby)
External Connections	D-sub 15-pin, D-sub 9-pin, Type B socket USB, DC Power-in
Options / Features	N/A
Viewable Size	376 mm x 301 mm (19" diagonal)
Display Resolution	1280 x 1024
Dimensions (W x H x D)	17.0" x 14.2" x 2.5" (432.9 mm x 360.3 mm x 64.4 mm)
Display Weight	12.7 lbs (5.8 kg) net; 18.3 lbs (8.3 kg) shipping
Shipping weight	N/A
Product Approvals	UL/c-UL, FCC-Class B, TUV-T mark, CE, RoHS
Operating Temperature	0° to +50°C (32° to 122°F)
Service and Support/Warranty	3-Year Customer First™ Warranty featuring FREE 2-Day Advance Replacement (US only)
VESA Compatible/Location	Compatible with 100 mm VESA mounting standard

For more information, please visit www.planar.com

Specifications are subject to change without notice.

Specification Report Date: 4/2/2013

(c)Copyright 2013 Planar Systems, Inc. All rights reserved



205 Westwood Ave, Long Branch, NJ 07740

Phone: 866-94 BOARDS (26273) / (732)-222-1511

Fax: (732)-222-7088 | E-mail: sales@touchboards.com