

4K LARGE FORMAT LCD DISPLAY FEATURES COMPARISON



Planar Standard 4K Models

UJTAMD	Planar [®] UltraRes [™] Series		Planar [®] QE Series		Planar [®] EP Series		Planar [®] EPX Series		Planar [®] PS Series 4K		Planar [®] Simplicity [™] Series 4K	
Sizes	75", 86", 98"		75", 86", 98"		50", 58", 65"		100"		50", 55", 65"		43", 50", 55", 65", 75", 86"	
Brightness	500 nits		500 nits (75", 86") 400 nits (98")		500 nits		700 nits		550 nits (50", 55") 450 nits (65")		350 nits (43", 50", 55", 65") 410 nits (75", 86")	
BackLight type: Edge-lit LED LCD		75", 86"		75", 86"	✓	50", 58"					✓	
BackLight type: Direct-lit LED LCD	✓	98"	✓	98"	✓	65"	✓		✓			
Orientation	✓	Landscape, Portrait		Landscape, Portrait	✓	Landscape, Portrait	✓	Landscape, Portrait	✓	Landscape, Portrait	✓	Landscape
ERO protection *	✓	Gorilla Glass										
Profile depth	✓	<4", ADA compliant										
Outputs: DisplayPort 1.2	✓											
Inputs: OPS	✓				✓		✓				✓	65", 75", 86"
Inputs: DisplayPort 1.2	✓		✓		√		✓		✓		✓	65", 75", 86"
Inputs: HDMI 1.4 (4K @ 30Hz)	✓				✓		✓					
Inputs: HDMI 2.0 (4K @ 60Hz)	✓				✓		✓		✓		✓	
Inputs: HDCP 2.2	✓				✓		✓		✓		✓	
Inputs: LAN RJ45, RS232	✓				✓		✓		✓		✓	
Inputs: USB	✓	via OPS			✓	via OPS	✓	via OPS	✓	Embedded Player	✓	via OPS (65", 75", 86")
Image adjustments by source	✓				✓	Limited	✓	Limited				
Scheduling	✓				✓		✓				✓	
Presets	✓				✓	Limited	✓	Limited				
Media playback		via OPS			✓	via OPS	✓	via OPS	✓	USB (Limited) Android OS	✓	USB
WiFi									√	Select Models		
Browser	✓	via OPS			✓	via OPS	✓	via OPS			✓	
SNMP 2	✓		✓		✓		✓		✓			
Remote monitoring ³ (email notifications)	✓		✓		✓		✓		✓			
Mobile app	✓											
Video wall tiling	✓											
Serviceability ¹ (kickstand, removable tray)	✓											
Audio speakers	✓				✓		✓		✓		✓	
24x7 operation	✓				✓		✓		√			
Metal enclosure	✓				✓		✓				✓	75", 86"
Redundant power ⁴	✓											
Warranty included	✓	3-year	✓	3-year	✓	3-year	✓	3-year	✓	3-year	✓	2-year
U.S. TAA Compliant	✓		✓		✓		✓		✓			
Ideal applications		Public spaces Digital branding & signage Collaboration Corporate Control Rooms	[Digital branding & signage Collaboration Education Retail Public spaces		Digital branding & signage Corporate spaces Control rooms Retail Public spaces		oigital branding & signage corporate spaces Control rooms Retail Public spaces		Digital branding & signage Retail Museums Public Spaces		Retail Medical offices Reception areas Restaurants Hospitality

^{*}ERO protection — proprietary, protective bonded glass process that improves contrast and overall durability for high-traffic environments

¹Field Serviceability — ability to swap most primary electronic components in the field

²SNMP — (Simple Network Managing Protocol) allows monitoring and control of the display over a network

³Remote monitoring — subset of SNMP; diagnostics for individual display components and display settings

⁴Redundant power — reduces downtime in the event of a power supply failure



Planar Interactive Touch 4K Models

	Planar [®] HB Series Huddle Board	Planar [®] UltraRes [™] Series Touch	Planar [®] QE Series Touch	Planar [®] EP Series Touch	Planar [®] EPX Series Touch	Planar [®] PS Series 4K Touch	
Sizes	75", 86"	75", 86", 98"	75", 86", 98"	50", 58", 65"	100"	50", 55", 65"	
Touch technology	In-Cell Projected Capacitive (PCAP)	Infrared (IR), HID- compliant	Infrared (IR), HID- compliant	Infrared (IR), HID- compliant	Infrared (IR), HID- compliant	Infrared (IR), HID- compliant	
Touch points, simultaneous	20 points	6 points (32 w/ driver)	20 points	20 points	20 points	20 points	
Fine Tip Stylus Support	Passive & Active (included)				3mm stylus (included)		
Brightness (with touchscreen)	350 nits	450 nits	450 nits (75", 86") 360 nits (98")	450 nits	630 nits	500 nits (50", 55") 400 nits (65")	
BackLight type: Edge-lit LED LCD		75", 86"	75", 86"	50", 58"			
BackLight type: Direct-lit LED LCD	✓	98"	98"	65"	✓	✓	
Orientation	Landscape	✓ Landscape, Portrait	Landscape, Portrait (75", 86")	✓ Landscape, Portrait	✓ Landscape, Portrait	✓ Landscape, Portrait	
ERO protection*	2mm glass w/ AG coating	✓ Gorilla Glass	✓ Gorilla Glass	3mm glass w/ AG coating	4mm glass w/ AG coating	4mm glass w/ AG coating	
Profile depth		✓ 4.1"					
Outputs	HDMI	✓ DisplayPort 1.2	-	-		-	
Inputs: OPS	✓	✓	-	✓	✓		
Inputs: DisplayPort 1.2	✓	✓	✓	✓	✓	✓	
Inputs: HDMI 1.4 (4K @ 30Hz)		✓	✓	✓	✓	-	
Inputs: HDMI 2.0 (4K @ 60Hz)	✓	✓	✓	✓	✓	✓	
Inputs: HDCP 2.2	✓	✓	✓	✓	✓	✓	
Inputs: LAN RJ45, RS232	✓	✓	✓	✓	✓	✓	
Inputs: USB	✓	✓ via OPS		✓ via OPS	via OPS	 Embedded Player 	
Image adjustments by source		✓	✓	Limited	✓ Limited		
Scheduling		✓	✓	✓	✓		
Presets		✓		✓ Limited	Limited		
Media playback	USB Android OS	via OPS		✓ via OPS	via OPS	USB (Limited) Android OS	
Browser	✓	via OPS		✓ via OPS	via OPS		
WiFi	✓	-	-			Select Models	
SNMP ²	✓	✓	✓	✓	✓	✓	
Remote monitoring ³ (email notifications)		✓	✓	✓	✓	✓	
Mobile app		✓	-	-		-	
Video wall tiling		✓					
Serviceability ¹ (kickstand, removable tray)		✓					
Audio speakers	✓	✓	✓	✓	✓	✓	
24x7 operation		✓	✓	✓	✓	✓	
Metal enclosure	✓	✓	✓	✓	✓	Metal front bezel	
Redundant power ⁴		✓					
Warranty included	✓ 3-year	✓ 3-year	✓ 3-year	✓ 3-year	✓ 3-year	✓ 3-year	
U.S. TAA Compliant	✓	✓	✓	✓	✓	✓	

 $^{{}^{\}star}\text{ERO protection } -\text{proprietary, protective bonded glass process that improves contrast and overall durability for high-traffic environments}$

¹Field Serviceability — ability to swap most primary electronic components in the field

²SNMP — (Simple Network Managing Protocol) allows monitoring and control of the display over a network

³Remote monitoring — subset of SNMP; diagnostics for individual display components and display settings

⁴Redundant power — reduces downtime in the event of a power supply failure