

Planar industrial open frame displays deliver cost-effective and high quality display solutions for OEMs and system integrators requiring displays to be integrated into an application. Planar open frame monitors are available in a wide range of sizes, resolutions and brightness, making them ideal for commercial applications from retail to gaming, hospitality to kiosks.



Planar LA-Series

The Planar LA-Series features 15, 17, 19 and 22-inch size open-frame monitors that deliver a high quality display solution for OEMs and integrators to easily integrate into indoor kiosk enclosures. The Planar LA-Series family includes models with touch technology, including resistive, surface acoustic wave, capacitive or P Cap.

PLANAR LA-SERIES (TOUCH MODELS)

Model/Part Number	LA1710RTS (997-6292-00LF)	LA1950RTR (997-6288-00LF) LA1950RTC (997-6128-00LF) LA1950RTS (997-6289-00LF)	LA2250RTPW (997-7070-00)
Viewable Size	17"	19"	22"
Touch Screen Type (Interface)	SAW (LA1710RTS) (Dual Serial/USB)	5-wire Resistive (LA1950RTR) Surface Capacitive (LA1950RTC) SAW (LA1950RTS) (Dual Serial/USB)	Projected Capacitive (USB)
Number of Touch Points	1	1	2
Driver Compatibility	Windows® 7, VISTA, XP*	Windows® 7, VISTA, XP*	Windows® 7, VISTA, XP*
Display Resolution	1280 x 1024	1280 x 1024	1920 x 1080
Brightness (w/o touchscreen)	350 cd/m ²	250 cd/m ²	250 cd/m ²
Contrast Ratio (Typical)	1000:1	800:1	1000:1
Response Time (Typical)	5 ms	5 ms	14 ms
Viewing angle (Typical)	150° H, V	160° H, V	178° H, V
Video Inputs	VGA/DVI	VGS	VGA/DVI
Power Consumption	40 Watt (LA1710RTS)	25 Watt	27 Watt
Warranty	3 year advance exchange	3 year advance exchange	3 year advance exchange

PLANAR LA-SERIES (NON-TOUCH MODELS)

Model/Part Number	LA1500R (997-5803-01LF)	LA1710R (997-2808-01LF)	LA1950R (997-6179-00LF)
Viewable Size	15"	17"	19"
Display Resolution	1024 x 768	1280 x 1024	1280 x 1024
Brightness	250 cd/m ²	350 cd/m ²	250 cd/m ²
Contrast Ratio (Typical)	600:1	1000:1	800:1
Response Time (Typical)	8 ms	5 ms	5 ms
Viewing Angle (Typical)	160° H, V	155° H, 150° V	160° H, V
Video Inputs	VGA	VGA/DVI	VGA
Power Consumption	30 Watt	60 Watt	25 Watt
Warranty	3 year advance exchange	3 year advance exchange	3 year advance exchange



Planar LC-Series

Planar LC-Series open frame monitors are available in 15, 19 and 26-inch sizes and provide full sunlight viewability, delivering an ideal display solution for outdoor kiosks and outdoor digital signage. Planar LC-Series displays are designed to perform in a wide range of operating temperatures and provide optimal viewing as lighting conditions change.

PLANAR LC-SERIES

Model/Part Number	LC1503R (997-6329-00LF) LC1503R-C (997-6359-00LF)	LC1913RTZ-C (997-5361-03LF)	LC2600R-C (997-6050-01LF)
Viewable Size	15"	19"	26"
Display Resolution	1024 x 768	1280 x 1024	1366 x 768
Brightness	1600 cd/m ²	1000 cd/m ²	1000 cd/m ²
Contrast Ratio (Typical)	600:1	500:1	800:1
Response Time (Typical)	8 ms	20 ms	5 ms
Viewing Angle (Typical)	160° H, V	140° H, V	60° H, V
Video Inputs	Analog	VGA/DVI	DVI only
Power Consumption	20 Watt	80 Watt	90 Watt
Features/Variants	LC1503R-C - Integrated cooling kit	Integrated IR Touch and cooling kit, 1 touch point	Integrated cooling kit Power cord and DVI cable sold separately



Planar LX-Series Ruggedized Displays

Designed for durability, reliability, and optimal performance in extreme environments, Planar's LX-Series ruggedized displays are ideal for mining, heavy industrial, emergency response, marine and military applications. Features include an infrared touchscreen, a wide range of operating temperature, and IP rated waterproof and dustproof enclosures. Optically-bonded strengthened glass boosts durability and contrast for at-a-glance readability, and the LED backlight reduces power consumption, improves EMI performance, and extends the life of the display.

PLANAR LX-SERIES

Model/Part Number	LX0850PTI (997-5691-01LF)	LX1250TI (997-6186-01)	LX1251TI (997-6192-00LF)
Viewable Size	8.4"	12.1"	12.1"
Touchscreen Type (interface)	Infrared (IR), (USB)	Infrared (IR), (USB)	Infrared (IR), (USB)
Number of Touch Points	1	1	1
Display Resolution	800 x 600	1024 x 768	1024 x 768 XGA
Video Input	VGA	VGA	VGA
External Connections	Breakout cable - 37-pin sealed connector to VGA/USB/power connectors	Single military-grade connector with combined VGA/USB/power/audio	VGA, USB, power
Brightness (Typical)	> 700 cd/m ² (typical)	650 cd/m ²	650 cd/m ²
Contrast Ratio (Typical)	600:1	600:1	600:1
Viewing Angle (Typical)	160° H, 140° V	140°H, 120°V	140°H, 120°V
Response Time (Typical)	25 ms	25 ms	25 ms
Warranty	1 year	1 year	1 year

For full product specs, visit www.planar.com



When image experience matters.

www.planar.com
sales@planar.com
 1-866-475-2627



Planar is a trademark of Planar Systems, Inc. All other trade and service marks are the property of their holders.

Copyright© 2014 Planar Systems, Inc. All rights reserved. This document may not be copied in any form without written permission from Planar Systems, Inc. Information in this document is subject to change without notice. 02/14