



## Planar VS Series

### LED Video Wall Displays

- ▶ *2.5, 3.9 & 4.8mm pixel pitches*
- ▶ *Fast, secure assembly, tear-down & transport*
- ▶ *Magnetically-attachable & ratcheting quick lock*
- ▶ *Curve video walls +/- 5 degrees*



Planar<sup>®</sup> VS Series indoor LED video wall displays take event viewing experiences to the next level. With strikingly crisp, bright images that entice audiences at viewing distances as close as 14 feet, and mechanical elements designed to hold up to frequent, fast assembly and teardown, the Planar VS Series is the right choice for concerts, exhibitions or tradeshows.

---

### Set Up Without Breaking Down

Strong magnets on top of the interlocking magnesium alloy-framed cabinets are easy to understand and offer reassurance. Cabinets are lightweight and have features to facilitate single-person setup. When they're in use, the modular design offers full front or rear access, making any needed maintenance and servicing a breeze.



# Product Highlights



## Universal Hardware

Hang or stack Planar VS Series cabinets with universal header and floor stand hardware that makes it easy to adjust installation styles when event environments require something unexpected.



## Curve Capable

On-board angle blocks enable connected Planar VS Series cabinets to effortlessly, and securely, form convex or concave video walls with up to 5 degrees of curve. to seemingly envelope a stage.

# Specifications

Model	VSI2.5	VSI3.9	VSI4.8
<b>Pixel Pitch (mm)</b>	2.5	3.91	4.81
<b>Resolution</b>	200 x 200	128 x 128	104 x 104
<b>Pixel Density</b>	160,000/m <sup>2</sup>   14,864/ft <sup>2</sup>	65,536/m <sup>2</sup>   6,088/ft <sup>2</sup>	43,264/m <sup>2</sup>   4,019/ft <sup>2</sup>
<b>Power Consumption, Max (watts)</b>	155/Cabinet   620/m <sup>2</sup>	140/Cabinet   560/m <sup>2</sup>	
<b>Cabinet Size (WxHxD)</b>	500 x 500 x 77mm   19.69 x 19.69 x 3.03in		
<b>Line Voltage</b>	100-240V AC, 50/60Hz		
<b>Cabinet Weight</b>	7kg   15.43lbs		
<b>Brightness Max, Calibration On</b>	1,000 cd/m <sup>2</sup>		
<b>Contrast Ratio</b>	4,000:1		
<b>LED Refresh Rate</b>	3,840Hz		
<b>Color Temperature, Adjustable</b>	3,000 - 10,000k		
<b>Viewing Angle Horizontal, Vertical</b>	140°, 140°		
<b>Service Access</b>	Front (module) / Rear		
<b>Environment</b>	Indoor		
<b>Operating Temperature/Humidity</b>	-20° to 40° C   4° to 104° F		
<b>Installation</b>	Hanging, Standing, Wall Mounted		
<b>Controller</b>	S6F		

For more information, click to visit: [www.planar.com/vs](http://www.planar.com/vs)

Planar is a trademark of Planar Systems, Inc. All other trademarks and service marks are property of their holders. Copyright © 2022 Planar Systems, Inc. All rights reserved. This document may not be copied in any form without permission from Planar. Information in this document is subject to change without notice. 4/2022