



# Planar VM Series

## LCD Video Wall

- ▶ *55" Full HD LCD displays*
- ▶ *Tiled bezel widths of 0.88, 2.6 or 3.5mm*
- ▶ *500 & 700 nit brightness*
- ▶ *24x7 reliability*




Planar<sup>®</sup> VM Series LCD video wall displays deliver a feature-rich, ENERGY STAR<sup>®</sup> Certified solution for always-on and high ambient light applications. It offers multiple tiled bezel widths and brightness options in addition to high reliability, to meet the video wall digital signage demands of applications such as retail, hospitality, corporate lobbies, casinos and museums.



### Always-On Reliability

Planar VM Series is designed for mission-critical environments where displays need to withstand extended or continuous operation and deliver exceptional performance day and night.



### Orientation Versatility

The displays enable greater creativity in content development as they can be mounted in landscape orientation for common Full HD or 4K content resolutions, or in portrait orientation for a wider array of deployment environments and applications.

# Off-the-Shelf Video Walls

Planar® VM Complete™ is a pre-packaged solution that combines everything necessary to more-quickly select and deploy an ENERGY STAR® Certified, 24x7 LCD video wall. It removes the challenge of separately collecting everything; simply pick the 4K 2x2, or 6K 3x3 array and tiled bezel width that works best in the application. Available in 0.88mm or 3.5mm tiled bezel widths.



## Specifications

Model	VM55MX-M2	VM55LX-M2	VM55MX-X2	VM55LX-X2	VM55LX-U2
<b>Screen Diagonal</b>	55"				
<b>Native Resolution</b>	1920 x 1080				
<b>Bezel Width</b>	0.44mm even		1.7mm (left/top) 0.9mm (right/bottom)		2.25mm (left/top) 1.25mm (right/bottom)
<b>Tiled Bezel Width</b>	0.88mm		2.6mm		3.5mm
<b>Dimensions without handles (W x H x D)</b>	47.7" x 26.8" x 3.8"   1,210.5 x 681.2 x 97.1mm		47.8" x 26.9" x 3.8"   1,212.2 x 683.3 x 96.5mm		47.8" x 26.9" x 3.9" 1,213.4 x 684.2 x 98.0mm
<b>Display Technology</b>	IPS				
<b>Backlight</b>	D-LED with Local Dimming				
<b>Contrast Ratio Dynamic</b>	140,000:1	100,000:1	140,000:1	100,100:1	20,000:1
<b>Full Viewing Angle</b>	178°				
<b>ENERGY STAR® Certified</b>	Yes	—	Yes		
<b>Brightness (cd/m<sup>2</sup> or nits)</b>	700	500	700	500	500
<b>Inputs</b>	DisplayPort 1.2 in x 1, DisplayPort out, HDMI 2.0 in x 2 (HDCP 2.2), HDMI out, OPS x 1, OPS USB 2.0 x 2, OPS USB 3.0 x 1				
<b>OPS Slot</b>	Yes				
<b>Control</b>	IR, RS232, LAN, Keypad				
<b>Image Scaling</b>	4K at 60Hz upscaling and downscaling				
<b>Speakers</b>	10W x 2 built-in				
<b>Mounting</b>	VESA 400 x 400, Back				
<b>Orientation</b>	Landscape or Portrait				
<b>Regulations</b>	FCC Class A, cTUVus, CE				

For more information, click to visit: [www.planar.com/vm](http://www.planar.com/vm)

Planar is a trademark of Planar Systems, Inc. All other trademarks and service marks are property of their holders. Copyright © 2022 Planar Systems, Inc. All rights reserved. This document may not be copied in any form without permission from Planar. Information in this document is subject to change without notice. 4/2022