



Made in the  
United States of America

## Features

- Provides physical protection, with conductive material providing reliable path-to-ground
- Many sizes available
- Shipped knocked-down; easy to assemble
- Conductive  $1 \times 10^2$  to  $< 1 \times 10^5$  ohms material provides reliable path-to-ground
- Superior strength and durability; made from extruded, high impact polypropylene materials
- Chemical and moisture resistant
- Ideal for use where corrugated and/or paper products cannot be used
- Economical alternative to injection molded products
- Reusable, ensuring best value\*
- Made in the United States of America

## Specifications

Properties	Typical Values
Resin Type	Polypropylene
Conductive	Permanently
Surface Resistance	$1 \times 10^2$ to $< 1 \times 10^5$ ohms per ANSI/ESD STM11.11 and ESD TR53
Humidity Independent	Yes
Temperature Tolerance	-17° F to +230° F
Melting Point	324° F

Item	L x W x D (IN)	L x W x D (MM)
<a href="#">38900</a>	12 x 2 x 4	305 x 51 x 102
<a href="#">38901</a>	12 x 4 x 4	305 x 102 x 102
<a href="#">38902</a>	12 x 6 x 4	305 x 152 x 102
<a href="#">38903</a>	12 x 8 x 4	305 x 203 x 102
<a href="#">38904</a>	18 x 4 x 4	457 x 102 x 102
<a href="#">38905</a>	18 x 6 x 4	457 x 152 x 102
<a href="#">38906</a>	18 x 8 x 4	457 x 203 x 102
<a href="#">38907</a>	24 x 4 x 4	610 x 102 x 102
<a href="#">38908</a>	24 x 6 x 4	610 x 152 x 102
<a href="#">38909</a>	18 x 2 x 4	457 x 51 x 102
<a href="#">38910</a>	24 x 2 x 4	610 x 51 x 102
<a href="#">38911</a>	12 x 12 x 4	305 x 305 x 102
<a href="#">38912</a>	18 x 12 x 4	457 x 305 x 102

### RoHS 2 and REACH Compliance Statement

None of the RoHS 2 restricted materials or REACH substances of very high concern as of 2013/06/20 are intentionally added in manufacturing this product. Ref: European Union Directive 2011/65/EU and Regulation (EC) No. 1907/2006/CE. See Protektive Pak [Limited Warranty at ProtektivePak.com](#).

Per Packaging standard ANSI/ESD S54.1 section 6.1. Inside an ESD Protected Area "Packaging used within an EPA (that satisfies the minimum requirements of ANSI/ESD S20.20) shall be:

1. Low charge generation.
2. Dissipative or conductive materials for intimate contact."

*Unless otherwise noted, tolerance  $\pm 10\%$*

Specifications and procedures subject to change without notice.

## Plastek™ Open Bin Boxes

**PROTEKTIVE PAK**  
13520 MONTE VISTA AVENUE, CHINO, CA 91710  
PHONE (909) 627-2578  
[ProtektivePak.com](#)

**DRAWING NUMBER**  
38900

**DATE:**  
January  
2014

# PROTEKTIVE PAK