

## 20 Liter Heated Circulator



AD20H200

### Key Specifications

Description	200, 20 L Htg. Circulator
Controller Type	Advanced Digital
Display	3.75" Touch-Pad LCD
Connectivity	Ethernet, USB A & B, RS232/addressable RS485, External Temperature Probe
Languages Supported	4: French, German, Spanish, English
Swivel 180 Rotating Controller	Yes
Working Temperature Range °C	Ambient +10° to 200°
Temperature Stability °C	±0.01°
Fluid Optimization/Specific Heat Tuning	Automatic and/or user-adjustable
Temperature Calibration Capability	1-point
Working Access (L x W x D) (cm)	25 x 31.6 x 14 cm
Pump Type	Pressure/Suction
External Temperature Control Capability	Yes

---

Flammability Class (DIN 12876-1) III (FL)

## Key Features

Advanced Digital Controller

### Key Features

- Intuitive 3.75" (9.5 cm) display with touch-pad control
- 4 languages: French, German, Spanish, English
- Swivel 180™ Rotating Controller
- On-board connectivity: USB-A & B, Ethernet, RS-232/RS-485 and external temperature probe
- On-screen prompts
- Automatic performance optimization and specific heat tuning
- Single-point calibration capability

## Common Specifications

Working Temperature Range °F	Ambient + 20° to 392°
Working Temperature Range °C	Ambient +10° to 200°
Reservoir Capacity (gallons)	5.28
Reservoir Capacity (liters)	20
Reservoir/Tank Material	Stainless Steel
Reservoir Cover	Included
DuraTop	Yes
LidDock	Yes
Working Access (L x W x D) (inches)	9.85 x 12.45 x 5.5 in
Working Access (L x W x D) (cm)	25 x 31.6 x 14 cm
Temperature Stability °F	±0.02°
Temperature Stability °C	±0.01°
Display	3.75" Touch-Pad LCD
Display Resolution (Set)	0.01
Display Resolution (Read)	0.01
Pump Type	Pressure/Suction
Pump Speed	Variable
Process Connections	1/4" (F) NPT
External Temperature Control Capability	Yes

Flammability Class (DIN 12876-1)	III (FL)
Over-Temperature Protection / Failsafe Heater Control	Yes
Low Liquid Level Protection	Yes
Reservoir Drain	Yes
Cooling Coil	Yes
Included Software	PolyTemp Viewer, USB driver
Maximum Ambient Temperature °F	95°
Maximum Ambient Temperature °C	35°
Overall Dimensions (L x W x H) (inches)	24 x 16.5 x 16.6 in
Overall Dimensions (L x W x H) (cm)	61 x 41.9 x 42.2 cm
Environmental Compliance	RoHS, WEEE
Shipping Weight (pounds)	70.0
Shipping Weight (kilograms)	31.7
Catalog Page Number	56-57

## 60 Hz Only

Part Number	AD20H200-A11B
Maximum Pressure (psi)	4.3
Maximum Pressure (bar)	0.30
Maximum Pressure Flow Rate (gpm)	5.30
Maximum Pressure Flow Rate (l/min)	20.1
Maximum Suction Flow Rate (gpm)	3.9
Maximum Suction Flow Rate (l/min)	14.7
Included Hardware	Nylon hose adapters for 3/8", 1/4", and 3/16"
Heater Wattage	1100
Electrical Requirements (VAC/Hz/Ph/A)	120/60/1/10
Regulatory Approvals	ETL

## 50 Hz Only

Part Number	AD20H200-A12E
Maximum Pressure (psi)	3.6
Maximum Pressure (bar)	0.25

Maximum Pressure Flow Rate (gpm)	4.40
Maximum Pressure Flow Rate (l/min)	16.7
Maximum Suction Flow Rate (gpm)	3.2
Maximum Suction Flow Rate (l/min)	12.2
Included Hardware	Nylon hose adapters for 3/8", 1/4", and 3/16", and 1/4" NPT to M16 adapter
Heater Wattage	2200
Electrical Requirements (VAC/Hz/Ph/A)	240/50/1/10
Regulatory Approvals	CE

© 2015 **PolyScience** 6600 W. Touhy Avenue, Niles, Illinois 60714-4516 USA

**Phone:** +1(847) 647-0611 or +1(800) 229-7569 **Fax:** +1(847) 647-1155

**Source URL (modified on 11/11/2014 - 17:56):** [https://www.polyscience.com/circulating-baths/20-liter-heated-circulator-](https://www.polyscience.com/circulating-baths/20-liter-heated-circulator-4)