

Cryoprecipitate Bath

Image:



6260MXCRY

Key Specifications

| | |
|------------------------------------|----------------------|
| Description | Cryoprecipitate Bath |
| Controller Type | Digital |
| Display | Two Digital Readouts |
| Working Temperature Range °C | Setpoint Fixed@ 4°C |
| Temperature Stability °C | ±0.1° |
| Temperature Calibration Capability | 1-point |
| Working Access (L x W x D) (cm) | 52.4 x 33 x 30.5 cm |

Key Features

CRYOPRECIPITATE BATH

Features

- Setpoint Fixed at 4°C
- Thaws up to 24 units of FFP or Whole Blood (WB) simultaneously
- Bright temperature and elapsed time displays
- Built-in over-temperature and flow alarms
- Calibration capability
- High efficiency fluid filter, removable air filter, reservoir drain
- Hinged polycarbonate gabled cover

Common Specifications

| | |
|-------------------------------------|----------------------|
| Working Temperature Range °C | Setpoint Fixed@ 4°C |
| Reservoir Capacity (gallons) | 13.8 |
| Reservoir Capacity (liters) | 52.24 |
| Reservoir/Tank Material | Stainless Steel |
| Reservoir Cover | Included |
| Cleanable Air Filter | Yes |
| Working Access (L x W x D) (inches) | 20.6 x 13 x 12 in |
| Working Access (L x W x D) (cm) | 52.4 x 33 x 30.5 cm |
| Temperature Stability °F | ±0.2° |
| Temperature Stability °C | ±0.1° |
| Display | Two Digital Readouts |
| Display Resolution (Set) | 0.1 |

| | |
|--|---------------------|
| Display Resolution (Read) | 0.1 |
| Over-Temperature Protection / Failsafe Heater Control | Yes |
| Low Liquid Level Protection | Yes |
| Reservoir Drain | Yes |
| Maximum Ambient Temperature °F | 95° |
| Maximum Ambient Temperature °C | 35° |
| Overall Dimensions (L x W x H) (inches) | 28 x 14.5 x 36.6 in |
| Overall Dimensions (L x W x H) (cm) | 71.1 x 37 x 93 cm |
| Shipping Weight (pounds) | 200.0 |
| Shipping Weight (kilograms) | 90.7 |
| Catalog Page Number | 75 |

50 Hz Only

| | |
|--|--------------|
| Part Number | 6250MYCRY30E |
| Electrical Requirements (VAC/Hz/Ph/A) | 240/50/1/6.3 |
| Regulatory Approvals | CE |

60 Hz Only

| | |
|--|----------------|
| Part Number | 6260MXCRY10C |
| Electrical Requirements (VAC/Hz/Ph/A) | 120/60/1/11.25 |
| Regulatory Approvals | TUV |

© 2015 **PolyScience** 6600 W. Touhy Avenue, Niles, Illinois 60714-4516 USA

Phone: +1(847) 647-0611 or +1(800) 229-7569 **Fax:** +1(847) 647-1155

Source URL (modified on 01/02/2019 - 14:56): <https://www.polyscience.com/specialty-product/cryoprecipitate-bath>