

5 Liter General Purpose Water Bath



WB05

Key Specifications

| | |
|------------------------------------|---------------------------------------|
| Description | Gen. Purpose Water Bath, Digital, 5 L |
| Display | 3.25" LCD |
| Working Temperature Range °C | Ambient +5° to 100° |
| Temperature Stability °C | ±0.1° |
| Temperature Calibration Capability | 1-point |
| Working Access (L x W x D) (cm) | 12.7 x 27.4 x 15.2 |
| Flammability Class (DIN 12876-1) | I (NFL) |

Key Features

Common Specifications

| | |
|------------------------------|----------------------|
| Working Temperature Range °F | Ambient +10° to 212° |
| Working Temperature Range °C | Ambient +5° to 100° |
| Reservoir Capacity (gallons) | 1.32 |
| Reservoir Capacity (liters) | 5 |
| Reservoir/Tank Material | Stainless Steel |

| | |
|--|--------------------|
| Reservoir Cover | Hinged Gable |
| Working Access (L x W x D) (inches) | 5 x 10.8 x 6 |
| Working Access (L x W x D) (cm) | 12.7 x 27.4 x 15.2 |
| Temperature Stability °F | ±0.2° |
| Temperature Stability °C | ±0.1° |
| Display | 3.25" LCD |
| Flammability Class (DIN 12876-1) | I (NFL) |
| Over-Temperature Protection / Failsafe Heater Control | Yes |
| Maximum Ambient Temperature °F | 104° |
| Maximum Ambient Temperature °C | 40° |
| Overall Dimensions (L x W x H) (inches) | 12 x 14.5 x 10.5 |
| Overall Dimensions (L x W x H) (cm) | 30.5 x 36.8 x 26.7 |
| Shipping Weight (pounds) | 14.0 |
| Shipping Weight (kilograms) | 6.4 |
| Catalog Page Number | 86-87 |

50 Hz Only

| | |
|--|--------------|
| Part Number | WB05A12E |
| Included Hardware | Sample Tray |
| Heater Wattage | 360 |
| Electrical Requirements (VAC/Hz/Ph/A) | 240/50/1/1.6 |
| Regulatory Approvals | CE |

© 2015 **PolyScience** 6600 W. Touhy Avenue, Niles, Illinois 60714-4516 USA

Phone: +1(847) 647-0611 or +1(800) 229-7569 **Fax:** +1(847) 647-1155

Source URL (modified on 01/10/2017 - 17:12): <https://www.polyscience.com/general-purpose-water-baths/5-liter-general-purpose-water-bath>