

Projectors

Product Specifications

SHORT THROW, ULTRA SHORT THROW AND EXTREME SHORT THROW PROJECTORS



PRM-32 Projector



PRM-35 projector



EST-P1 projector



UST-P1 projector

THIS DOCUMENT CONTAINS SPECIFICATIONS FOR

Projectors

DESCRIPTION

Choice of Extreme Short Throw, Ultra Short Throw or Short Throw projectors.

SYSTEM OVERVIEW

Installation

The installation of this product should be completed by a Promethean Certified Installer. Components supplied and minimum specifications stated have been tested and are required for optimal performance. Use of components not supplied by Promethean or not meeting minimum specifications may impact performance and affect warranty. Contact your Promethean partner or visit www.PrometheanKB.com for more information

Warranty

For Promethean Warranty Information and Terms and Conditions please visit: www.PrometheanWorld.com/Warranty

Support

Online Support for all Promethean Products available from: www.PrometheanKB.com

Touchboards

205 Westwood Ave, Long Branch, NJ 07740
Phone: 866-94 BOARDS (26273) / (732)-222-1511
Fax: (732)-222-7088 | E-mail: sales@touchboards.com

ActivBoard Systems/Boards SS 03/14 V6.0 US



©2014 Promethean Limited. All rights reserved. Promethean Ltd. is owner of a number of trademarks in several jurisdictions across the world. Any third-party product and company names are mentioned for identification purposes only and may be trademarks of their respective owners. †Applicable Terms and Conditions for warranty and support available at www.PrometheanWorld.com/ActivCare. All weights and dimensions approximate. Product Specifications are subject to change without notice. www.PrometheanWorld.com

Projectors

Product Specifications

PROJECTOR SPECIFICATIONS



| Model | PRM-32 (DLP) | PRM-35 (DLP) | EST-P1 (DLP) | UST-P1 (DLP) |
|--|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|
| Native Resolution | WXGA 4:3 (1024 x 768) | WXGA 16:10 (1280 x 800) | WXGA 16:10 (1280 x 800) | WXGA 16:10 (1280 x 800) |
| Compressed Resolution | up to 1080i | up to 1080i | up to 1080i | up to 1080i |
| Typical Colors | 16.77 million colors | 16.77 million colors | 16.77 million colors | 16.77 million colors |
| Aspect Ratio | Fill, 4:3, 16:9, Letter box, Native | Fill, 4:3, 16:9, Letter box, Native | Fill, 4:3, 16:9, Letter box, Native | Fill, 4:3, 16:9, Letter box, Native |
| Contrast Ratio | 2000:1 | 2000:1 | 2000:1 | 2000:1 |
| Brightness High | 2300 ANSI Lumens (220W) | 2500 ANSI Lumens (220W) | 2850 ANSI Lumens (230W) | 3000 ANSI Lumens (230W) |
| Brightness Normal | 2000 ANSI Lumens (190W) | 2100 ANSI Lumens (190W) | 2200 ANSI Lumens (200W) | 2500 ANSI Lumens (200W) |
| Throw Ratio | 0.52 | 0.52 | 0.19 | 0.35 |
| Focal Length | F=2.87 | F=2.86 | F=2.4 | F=2.5 |
| Projection Distance | 0.54m ~ 1.22m (21.3in ~ 48in) | 0.54m ~ 1.22m (21.3in ~ 48in) | 0.39m ~ 0.56m (15in ~ 22in) | 0.34m ~ 0.42m (13.4in ~ 16.5in) |
| Projection Screen Size | 1.27m ~ 2.79m (50in ~110in) | 1.27m ~ 2.79m (50in ~110in) | 1.98m ~2.79m (78in ~ 110in) | 2.03m ~ 2.5m (80in ~ 100in) |
| Lamp Type | 220W | 230W | 220W | 230W |
| Lamp Life High | 4000 | 4000 | 4000 | 5000 |
| Lamp Life Normal | 6000 | 6000 | 6000 | 8000 |
| Acoustic Noise High | 36dB (220W) | 36dB (220W) | 31dB (220W) | 36dB (220W) |
| Acoustic Noise Normal | 33dB (190W) | 33dB (190W) | 27dB (190W) | 29dB (190W) |
| Power Supply & Consumption High | 280W | 280W | 390W | 300W |
| Standby | <1W excluding RJ45 | <1W excluding RJ45 | <1W excluding RJ45 | <0.5W excluding RJ45 |

CONTINUED ON NEXT PAGE

ActivBoard Systems/Boards SS 03/14 V6.0 US

©2014 Promethean Limited. All rights reserved. Promethean Ltd. is owner of a number of trademarks in several jurisdictions across the world. Any third-party product and company names are mentioned for identification purposes only and may be trademarks of their respective owners. †Applicable Terms and Conditions for warranty and support available at www.PrometheanWorld.com/ActivCare. All weights and dimensions approximate. Product Specifications are subject to change without notice. www.PrometheanWorld.com

PROJECTOR SPECIFICATIONS (CONTINUED)



| Model | PRM-32 (DLP) | PRM-35 (DLP) | EST-P1 (DLP) | UST-P1 (DLP) |
|--------------------------------|--|---|--|--|
| Input/Output VGA | D-sub 15 (RGB) x 2 | D-sub 15 (RGB) x 2 | D-sub 15 (RGB) x 2 | D-sub 15 (RGB) x 2 |
| Video | Composite video (RCA) x | Composite video (RCA) x | Composite video (RCA) x | Composite video (RCA) x |
| S-Video | x1 | x1 | x1 | x1 |
| HDMI | None | HDMI V1.3 | HDMI V1.3 | HDMI V1.4a |
| Audio in | None | None | None | Mini jack x1 |
| Audio out | None | None | None | Mini jack x1 |
| Control terminals USB | x1 | x1 | x1 | x1 |
| RS-232 | None | x1 | x1 | x1 |
| RJ-45 | x1 | x1 | x1 | x1 |
| Promethean System Mount | Yes | Yes | Yes | Yes |
| Fixed | No | Yes | Yes | Yes |
| Adjustable | No | Yes | Yes | Yes |
| Mobile | No | No | Yes | No |
| Dimensions (w x d x h) | 306mm x 216mm x 97mm (12in x 8.5in x 3.8in) | 306mm x 275mm x 97mm (12in x 3.8in x 10.1in) | 354mm x 319mm x 157mm (13.9in x 12.6in x 6.1in) without mirror 354mm x 411mm x 219mm (13.9in x 16.1in x 8.6in) including mirror | 287.5mm x 374.5mm x 122.6mm without mirror 287.5mm x 374.5mm x 160mm including mirror |
| Weight | 2.7kg (6lb) | 2.7kg (6lb) | 9kg (19.8lb) | 4.8kg (10.6lb) |
| Colour | Silver | Silver | Silver | Dark Grey |
| Device Type | DLP | DLP | DLP | DLP |
| Focus | Manual Focus | Manual Focus | Manual Focus | Manual Focus |
| Zoom | Digital Zoom | Digital Zoom | N/A | N/A |
| Keystone Correction | Vertical: max ±15° | Vertical: max ±15° | Vertical: max ±15° | Vertical: max ±15° |
| Operating Temperature | 5°C ~ 35°C (41°F ~ 95°F) | 5°C ~ 35°C (41°F ~ 95°F) | 5°C ~ 35°C (41°F ~ 95°F) | 5°C ~ 35°C (41°F ~ 95°F) |
| Horizontal Scan Rate | 15Hz ~ 90kHz | 15Hz ~ 90kHz | 15Hz ~ 90kHz | 15Hz ~ 90kHz |
| Vertical Scan Rate | 50Hz ~ 85Hz | 43Hz ~ 85Hz | 43Hz ~ 85Hz | 24Hz ~ 120Hz |

ActivBoard Systems/Boards SS 03/14 V6.0 US



©2014 Promethean Limited. All rights reserved. Promethean Ltd. is owner of a number of trademarks in several jurisdictions across the world. Any third-party product and company names are mentioned for identification purposes only and may be trademarks of their respective owners. †Applicable Terms and Conditions for warranty and support available at www.PrometheanWorld.com/ActivCare. All weights and dimensions approximate. Product Specifications are subject to change without notice. www.PrometheanWorld.com

PROJECTOR SPECIFICATIONS (CONTINUED)



Model

PRM-32 (DLP)

PRM-35 (DLP)

EST-P1 (DLP)

UST-P1 (DLP)

Computer Compatibility

IBM PC and Compatibles; Apple Macintosh, iMac, and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)

IBM PC and Compatibles; Apple Macintosh, iMac, and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)

IBM PC and Compatibles; Apple Macintosh, iMac, and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)

IBM PC and Compatibles; Apple Macintosh, iMac, and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)

Video Compatibility

NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1035i), EDTV (480p, 575i), SDTV (480i, 576i)

NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1035i), EDTV (480p, 575i), SDTV (480i, 576i)

NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1035i), EDTV (480p, 575i), SDTV (480i, 576i)

NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1035i), EDTV (480p, 575i), SDTV (480i, 576i)

Security

Kensington Lock, Security cable bar option, pin code security, remote control operated only

Kensington Lock, Security cable bar option, pin code security, remote control operated only

Kensington Lock, Security cable bar option, pin code security, remote control operated only

Kensington Lock, Security cable bar option, pin code security, remote control operated only

On-screen menu

Arabic, Chinese (Simplified), Chinese (Traditional), Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Korean, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish

Arabic, Chinese (Simplified), Chinese (Traditional), Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Korean, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish

Arabic, Chinese (Simplified), Chinese (Traditional), Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Thai, Turkish

Arabic, Chinese (Simplified), Chinese (Traditional), Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Thai, Turkish

Advanced Features

3D Ready
 Crestron RoomView Express
 Quick Lamp Access
 Direct power on/off
 Closed Caption

3D Ready
 Crestron RoomView Express
 Quick Lamp Access
 Direct power on/off
 Closed Caption

3D Ready
 Crestron RoomView Express
 Quick Lamp Access
 Direct power on/off
 Closed Caption

3D Ready
 Crestron RoomView Express
 Quick Lamp Access
 Direct power on/off
 Closed Caption

Packed Contents List

Projector, Power cord, computer cable (D-sub15 – D-sub15), wireless remote, owner's manual (CD - ROM & Quick Start Guide)

Projector, Power cord, computer cable (D-sub15 – D-sub15), wireless remote, owner's manual (CD - ROM & Quick Start Guide)

Projector, Power cord, computer cable (D-sub15 – D-sub15), wireless remote, owner's manual (CD - ROM & Quick Start Guide)

Projector, Power cord, computer cable (D-sub15 – D-sub15), wireless remote, owner's manual (CD - ROM & Quick Start Guide)

Pack Weights and Dimensions

Box 1 of 1: 4.1kg (9lb)
 Dimensions: 408mm x 290mm x 197mm (16.1in x 11.4in x 7.8in)
 Contents: Projector

Box 1 of 1: 4.7kg (10.4lb)
 Dimensions: 408mm x 349mm x 189mm (16.1in x 13.7in x 7.4in)
 Contents: Projector

Box 1 of 1: 12.8kg (28.2lb)
 Dimensions: 516mm x 596mm x 356mm (20.3in x 23.5in x 14.0in)
 Contents: Projector

Box 1 of 1: 9kg (19.8lb)
 Dimensions: 440mm x 519mm x 291mm (17.3in x 20.4in x 11.5in)
 Contents: Projector

Warranty

For Promethean Warranty Information and Terms and Conditions please visit: www.PrometheanWorld.com/Warranty

Support

Online Support for all Promethean Products available from: www.PrometheanKB.com