

# Promethean® Distance Learning Bundle

## PRODUCT SPECIFICATIONS



### WEBCAM SPECIFICATIONS

|                                  |   |
|----------------------------------|---|
| Sensor                           | 1/2.7", CMOS, Effective Pixel: 2.07 M   |
| Lens                             | Focus: f=3.1 mm, FOV: 90 degree with distortion cancellation  |
| Shutter                          | 1/30s ~ 1/10000s  |
| White Balance                    | Auto  |
| Digital Noise Reduction          | 2D, 3D digital noise reduction  |
| Microphone                       | Omni-directional, dual mic array  |
| Privacy Shutter                  | Included  |
| Operating System Compatibility   | Windows 7, Windows 8.1, Windows 10 or later; macOS 10.10 or later; Chrome OS; Linux                 |
| Colour System/Compression        | H.264 / MJPEG   |
| Video Format                     | 1080p @ 30FPS/25FPS,<br>720p @ 30FPS/25FPS,<br>960 x 540p @ 30FPS/25FPS,<br>640 x 360 @ 30FPS/25FPS |
| USB Video Communication Protocol | UVC 1.0 ~ UVC1.5  |
| USB Interface                    | USB 2.0 Type A  |

### ENVIRONMENTAL

|                       |                                    |
|-----------------------|------------------------------------|
| Operating Temperature | 0°C to 40°C (32°F to 104°F)        |
| Storage Temperature   | -15°C to 55°C (-5°F to 131°F)      |
| Operating Humidity    | 20% to 80% non-condensing humidity |
| Storage Humidity      | 20% to 90% non-condensing humidity |

### COMPLIANCE & CERTIFICATION

|                          |                             |
|--------------------------|-----------------------------|
| Regulatory Certification | CE, FCC, IC, CB, RoHS, WEEE |
|--------------------------|-----------------------------|

### WARRANTY

Warranty terms and upgrade options vary by region. Contact your local reseller or distributor for information and visit [PrometheanWorld.com/Warranty](http://PrometheanWorld.com/Warranty).

### TRIPOD AND CABLE SPECIFICATION

|                               |   |
|-------------------------------|---|
| Material                      | Aluminium Alloy                                       |
| Max. operation height         | 1500 mm (59 in)                                       |
| Min. operation height         | 475 mm (18.7 in)                                      |
| Fold height                   | 505 mm (19.9 in)                                      |
| Max. load weight              | 3 kg (6.6 lb)   |
| Net weight                    | 1.2 kg (2.4 lb)                                       |
| Head Type                     | Three-way head Quick Release                          |
| Screw type                    | 6.4 mm (¼ in)   |
| Max. diameter of tube Section | 25 mm (1 in)<br>4                                     |
| USB Extension Cable           | USB-A 2.0 Male-Female Extension Cable<br>2 m (6.5 ft) |

### PACKED CONTENTS

|                   |  |
|-------------------|--|
| What's in the Box | Promethean Webcam x1<br>Promethean Tripod x1<br>USB-A Extension Cable x1<br>Quick Start Guide x1 |
|-------------------|--|

### PHYSICAL SPECIFICATIONS

|                   |  |
|-------------------|--|
| Packed Dimensions | 540 x 180 x 160 mm (21.3 x 7.1 x 6.3 in) |
| Net Weight        | 1.75kg (3.9 lbs)                         |
| Packed Weight     | 1.97 kg (4.34 lbs)                       |

### SUPPORT

For all Promethean products, visit [Support.PrometheanWorld.com](http://Support.PrometheanWorld.com).

## TECHNICAL DRAWINGS

