



\*Tray sold separately

### Features

- Finger notches in lids for easy lifting
- Constructed of impregnated corrugated material for greater durability
- Static dissipative surface Resistance of  $1 \times 10^6$  to  $< 1 \times 10^9$  ohms
- Buried shielding layer minimizes the potential of sloughing and abrasion contamination
- Made from 100% recycled material and is 100% recyclable
- Made in the United States of America

| Part Number           | For Use With                                  |
|-----------------------|---|
| <a href="#">37766</a> | <a href="#">37750</a>                         |
| <a href="#">37767</a> | <a href="#">37760</a> & <a href="#">37762</a> |
| <a href="#">37768</a> | <a href="#">37751</a>                         |
| <a href="#">37769</a> | <a href="#">37761</a> & <a href="#">37763</a> |

Meets the required limits of ANSI/ESD S20.20, and Packaging standard ANSI/ESD S541.

### SPECIFICATIONS

| Properties         | Typical Values   | Test Procedures/Method   |
|--------------------|--|--|
| Surface Resistance | $1 \times 10^6$ to $< 1 \times 10^9$ ohms  | ANSI/ESD STM11.11  |
| Sloughing Test     | Negligible surface damage at 10 cycles and <5% of surface damage at 200 cycles in Taber Abrasion Test. | ASTM D4060 at 70 rpm with CS-17 abrasive-coated wheels and 1000 grams load                                     |
| Recyclability      | No conductive particles abraded from surface<br>Complete recyclability of package                      | Rockwell International Test Report of January 8, 1992<br>Rockwell International Test Report of January 8, 1992 |



Specifications and procedures subject to change without notice.

### DROP IN LID, TEK-TRAY



PROTEKTIVE PAK  
 13520 MONTE VISTA AVENUE, CHINO, CA 91710  
 PHONE (909) 627-2578, FAX (909) 927-8444  
[ProtectivePak.com](http://ProtectivePak.com)

**DRAWING NUMBER**  
 37766

**DATE:**  
 August  
 2015