



Features

- Economical, efficient method of shipping and storing static sensitive electronic devices.
- Constructed from conductive extruded high impact polypropylene plastic; provides superior strength and durability
- Meets ANSI/ESD S20.20 and Packaging Standard ANSI/ESD S541
- Chemical and moisture resistant
- Ideal for use where corrugated and/or paper products cannot be used
- Economical alternative to injection molded products
- Ships flat, assembly required
- Made in the United States of America

SPECIFICATIONS

Properties	Typical Values
Resin Type	Polypropylene
Conductive	Inherently
Surface Resistance	1×10^2 to $< 1 \times 10^5$ ohms
Humidity Independent	Yes
Temperature Tolerance	-17° F to +230° F
Melting Point	324° F

ITEM	Size ID - L x W x D (IN)
38840	6-3/16" x 6" x 1-1/2"
38842	7" x 5" x 1-1/2"
38845	7" x 5" x 2-1/2"
38848	10-1/2" x 8-1/2" x 1-1/2"
38851	10-1/2" x 8-1/2" x 2-1/2"
38854	12-1/2" x 10-1/2" x 2-1/2"

Dimensional tolerances:
+/- 1/8" unless otherwise specified

RoHS, REACH, and Conflict Minerals Statement:
See the Desco Industries ROHS, Reach and Conflict Minerals Statement
Descoindustries.com/ROHS3.aspx
See the Protektive Pak Limited Warranty
Protektivepak.descoindustries.com/Limited-Warranty.aspx



Made in the
United States of America

Per Packaging standard ANSI/ESD section 6.2 Outside an EPA "Transportation of sensitive products outside of an EPA shall require packaging that provides:

1. Low charge generation.
2. Dissipative or conductive materials for intimate contact.
3. A structure that provides electrostatic discharge shielding."

Specifications and procedures subject to change without notice.

PLASTEK™ CIRCUIT BOARD SHIPPERS

PROTEKTIVE PAK

PROTEKTIVE PAK
13520 MONTE VISTA AVENUE, CHINO, CA 91710
PHONE (909) 627-2578
ProtektivePak.com

DRAWING NUMBER
38840

DATE:
January
2019