



Lid sold separately

Features

- Durable corners allow the containers to be stacked securely without slipping
- Includes wire frame for stability and extra strength
- Provide physical and ESD protection; conductive material has a more reliable path-to-ground
- Rs: 1×10^2 to $< 1 \times 10^5$ ohms per ANSI/ESD STM11.11, meets ANSI/ESD S20.20 and Packaging standard ANSI/ESD S541
- Plastek™ Drop-in lid available
- Product ships assembled



Specifications

Properties	Typical Values
Resin Type	Polypropylene
Conductive	Permanently
Surface Resistance	1×10^2 to $< 1 \times 10^5$ ohms per ANSI/ESD STM11.11
Humidity Independent	Yes
Temperature Tolerance	17° F to +230° F
Melting Point	324° F

Part Number	Box Size - L x W x D	Lid
39175	17 x 13 x 8-3/4	39183
39176	17 x 13 x 10-3/4	39183
39177	18-3/8 x 12-3/8 x 12-3/4	39185
39178	18-5/8 x 15 x 12	39186
39179	22-7/8 x 12-7/8 x 6	39184
39180	22-7/8 x 12-7/8 x 10	39184
39181	22-7/8 x 12-7/8 x 12-5/8	39184
39182	22-7/8 x 12-7/8 x 15-1/4	39184



Made in the
United States of America

If not otherwise noted, tolerance $\pm 10\%$

Specifications and procedures subject to change without notice.

Plastek™ Stackable Storage Containers

PROTEKTIVE PAK

PROTEKTIVE PAK
13520 MONTE VISTA AVENUE, CHINO, CA 91710
PHONE (909) 627-2578
ProtektivePak.com

DRAWING NUMBER
39175

DATE:
July
2015