

Aquant (BLD5770)

Protimeter Non-Invasive Moisture Meter

The Aquant is a non-invasive rapid test moisture meter for a wide range of building and construction materials.

Features

- Measures up to 3/4" (19 mm) below the surface
- Adjustable auto off
- Audible tone
- Hold feature
- Backlit LCD display
- Color arc LED display
- User field calibration
- Over the air software upgrade
- Multilingual UI

Benefits

- Detects moisture directly in materials and below wall and floor coverings such as tile, wood and vinyl
- Not adversely affected by surface moisture such as condensation
- Dual display LCD and LED for easy reading
- Color changing LEDs to show moisture condition green (dry), yellow (at risk) and red (wet)

Applications

- Building survey
- Fire and flood construction
- Concrete and wood floor moisture measurement





Aquant Specifications

Dimensions (h x w x d)

7 in X 2.5 in X2.1 in (177 mm X 63 mm X 53 mm

Display 1

Digital LCD

Display 2

Multicolor LED arc - Green (dry), Yellow (at risk) and Red (wet)

Measurement Range

Non-invasive (RF) 60 to 999 (relative) Dry (green) — 60-169 At Risk (yellow) —170 - 199 Wet (red) — 200-999

Depth of Moisture

Up to 3/4 in (19 mm)

Case

Pouch with belt loop

Power

3V (2 x AA) 2700mAh

Gross Weight

240 gm

Warranty

2 years on mechanical or manufacturing defects. Does not include wearing part or accessories.

Part Number

BLD5770













Protimeter devices with Bluetooth are able to use the free Protimeter Connect App. The app allows users to record measurement readings and photos.



www.amphenol-sensors.com

© 2024 Amphenol Corporation. All Rights Reserved. Specifications are subject to change without notice. Other company names and product names used in this document are the registered trademarks or trademarks of their respective owners.

