

Interactive LED Touchscreen

QIT Pro Series - 42" / 55" / 65" / 70" / 84"













FEATURE HIGHLIGHTS

- Multi-User
- 1080p HD resolution
- Best connectivity in class
- Ultra-fast touch response
- Integrated speakers
- Built-in PC (optional)
- Full-featured professional annotation software

For two Side Insert Test Configuration Larguage Solution May The View Side Insert Test Configuration Larguage Solution May For Insert Test Configuration Larguage Solution May Importance of Nutrition to Students Time Students Eat Carloteria Food per Week In the processes of the Circlery Yealth in Solveon Protectioning of 2 joint stem purpositional in a student Note grown for the food grown for disord or continuous and continuous and

Practical for **EDUCATION**

With an optional included PC and easy connections to hook up your own PC, accessing lessons is a synch.

Bring multiple students to the screen at once using our included software Flow!Works and it's many educational features to make quality interactive lessons.

The Street flatter flatter of the street fla

Front Monitor Controls



Built-In PC Ports:

WiFI Antenna, USB (A), LAN, VGA, Audio, Power Input



Sophisticated for **BUSINESS**

With the best connectivity in its class, the QIT Pro integrates seamlessly into any professional setting.

Our annotation software, Flow!Works is a great presentation tool, allowing presenters to annotate over slides in any software, including PowerPoint.



Right Ports:

2 VGA, 2 Audio, Composite, Component, S-Video, 2 HDMI, 2 USB (A & B)



Interactive LED Touchscreen



QIT Pro Series - 42" / 55" / 65" / 70" / 84"

FEATURE HIGHLIGHTS

- Multi-User
- 1080p HD resolution
- Best connectivity in class (IR) technology
- Integrated speakers
- Built-in PC (optional)
- Environmentally friendly

- Annotation software
- HDMI, VGA, Audio, S-Video,

Component, Composite, &

USB (A & B)

• Ultra-fast touch response



| Size | 42" | 55" | 65" | 70" | 84" | |
|---|--|---------------------------------------|--|---|--|--|
| Screen Type | TFT LCD with LED back lighting | | | | | |
| Display Area (H×V) | 930 x 523mm (36.6 x 20.5") | 1210 x 680mm (473 x 27") | 1428 x 804mm (56 x 32") | 1539 x 866mm (61 x 34") | 1860 x 1047mm (73 x 41") | |
| Resolution | · | 1920 x | 1080 | | 3840 x 2160 | |
| Brightness | 250-350 cd/m2 | 380 cd/m2 | 280-360 cd/m2 | 280-350 cd/m2 | 280-350 cd/m2 | |
| Response Time | 6.5ms | 6.5ms | 8ms | 4ms | 5ms | |
| Refreshing Frequency | 120Hz | 100Hz/120Hz | 120Hz | 100H | lz/120Hz | |
| View Angle | 178/178 | | | 176/176 | 178/178 | |
| CONNECTIVITY | 42" | 55" | 65" | 70" | 84" | |
| Built-in PC Ports (only on screens with built-in PC) | WiFi Antenna, USB (A), LAN, VGA, Audio, Power Input | | | | | |
| LED Screen Ports | 2 VGA, 2 HDMI, 2 Audio, Composite, Component, S-Video, 2 USB (A & B) | | | | | |
| TOUCH SYSTEM | 42" | 55" | 65" | 70" | 84" | |
| Infrared System | 6-pt operation 6-pt operation | | | | | |
| Response Time | <4ms(typ) | | | | | |
| Response Area | >Ф5mm | | | | | |
| Output Coordinate | 4096×4096 | | | | | |
| Communication Mode | Full-speed USB | | | | | |
| POWER | 42" | 55" | 65" | 70" | 84" | |
| Power Requirements | 100V-240V AC 50/60HZ | | | | | |
| Overall Power Consumption | < 120W(typ) | < 150W(typ) | < 250W(typ) | < 260W(typ) | < 500W(typ) | |
| Standby Power Consumption | < 0.5W | | | | | |
| SUPPLIED ACCESSORIES | 42" | 55" | 65" | 70" | 84" | |
| AC Power | r Cable/Quick Start Guide/\ | Writing Pen/Remote Cont | rol/VGA Cable/USB Cab | ole/Application and Drive | r Disk | |
| AMBIENT CONDITIONS | 42" | 55" | 65" | 70" | 84" | |
| Operation Temperature | 0℃ - 40℃ | | | 0°C - 50°C | | |
| Operation Humidity | 10% - 90% RH | | | 35% - 75% RH | -10% – 90% RH | |
| Storage Temperature | -20°C - 60°C | | | | | |
| Storage Humidity | 10% - 95% RH | | 10% - 90% RH | 10% - 70% RH | | |
| AMBIENT CONDITIONS | 42" | 55" | 65" | 70" | 84" | |
| Operation Temperature | 0°C - 40°C | | | 0°C - 50°C | | |
| Operation Humidity | 10% - 90% RH | | | 35% - 75% RH -10% - 90% RH | | |
| Storage Temperature | -20℃ - 60℃ | | | | | |
| Storage Humidity | 10% - 95% RH | | 10% - 90% RH | 10% - 70% RH | | |
| Dimension | 42" | 55" | 65" | 70" | 84" | |
| Net (W×D×H)/mm | 1066 x 100 x 659mm (42 x 4 x 26") | 1369 x 104 x 828mm (54 x 4 x 33") | 1591 x 110 x 961mm (63 x 4.3 x 38") | 1713 x 115 x 1035mm (67.4 x 4.5 x 41") | 1978 x 86 x 1186mm (78 x 7 x 47") | |
| Gross (W×D×H)/mm | 1190 x 281 x 823mm (47 x 11 x 32") | 1480 x 307 x 987mm (55 x 12 x 39") | 1720 x 235 x 1120mm (68 x 9 x 44") | 1860 x 260 x 1200mm (73 x 10 x 47") | 2180 x 340 x 1480mm (86 x 13 x 58") | |
| Net Weight | 33 kg (73 lbs) | 47 kg (104 lbs) | 66 kg (146 lbs) | 71 kg (157 lbs) | 116 kg (256 lbs) | |
| Gross Weight | 39 kg (86 lbs) | 55 kg (121 lbs) | 75 kg (165 lbs) | 83 kg (183 lbs) | 140 kg (309 lbs) | |







